

G51MA7-P09LCC0-0020
medi_snap, type_g5



General information

| | |
|--------------------------|---------------------|
| Part number | G51MA7-P09LCC0-0020 |
| Termination | solder |
| Size | 1 |
| Locking principle | break , push |
| Coding | a_key_medi |



Contact insert description

| | |
|-----------------------------|---------|
| Number of contacts | 9 |
| Contact type | sockets |
| Contact diameter | 05mm |
| Insulator material | peek |
| Wire cross section | 28_awg |
| Termination | solder |
| Termination diameter | 045mm |

reverse_gender_on_request

Technical information

| | | |
|---|-----------|---------------|
| Max. creepage and air clearance distance | 065_mm | |
| Nominal current single contact | 04_a | iec_60512_5_2 |
| Nominal current insert | 2,6 A | vde_0298_4 |
| Test voltage | 135_kv_dc | sae_13441 |

safety_text

Mechanical and environmental data

| | |
|------------------------------|----------|
| Degree of protection* | ip50 |
| Operating temperature | 50_120_c |
| Mating cycles | 5000 |

mated_unmated

Insulator materials MEDI-SNAP®

psu_peek

Material and surface treatments

| | |
|---------------------|---------------|
| Housing | psu_gray |
| Color option | red |
| Contact | cu_alloy_gold |

safety_text_2

ul_text

illustrative_text