6WWV-10-008 ✓ ACTIVE

Buchanan | Buchanan 6 Series

TE Internal #: 3-1546159-0

Barrier Strips, Tri-Barrier, Solderless Wire Wrap, Wire-to-Board, 10 Position, 9.53 mm [.375 in] Centerline, 1 Row, Buchanan 6 Series

View on TE.com >



Connectors > Terminal Blocks & Strips > Barrier Strips

Barrier Strip Style: Tri-Barrier

Bottom Termination Type: Solderless Wire Wrap

Connector System: Wire-to-Board

Number of Positions: 10

Centerline (Pitch): 9.53 mm [.375 in]

Features

Product Type Features

Block Style	Flat Bottom with standoffs
Connector System	Wire-to-Board
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Levels	1
Number of Positions	10
Number of Rows	1
Electrical Characteristics	
Operating Voltage	300 V
Body Features	
Primary Product Color	Black
Product Orientation	Vertical
Barrier Strip Style	Tri-Barrier
Contact Features	
PCB Contact Termination Area Plating Material	Tin

Termination Features

Contact Base Material

Contact Current Rating (Max)

Bottom Termination Type Solderless Wire Wrap

Copper Alloy

25 A



Screw Head Type Screw Plating Material Screw Material Screw Material Top Termination Type Wire Clamp Combo Head Mounting Options None Thread Size 6-32 Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Thermoplastic Centerline (Pitch) 9-53 mm(3.75 in) Dimensions Product Length 96.8 mm(3.811 in) Wire Size .3 – 3 mm² Operation/Application Circuit Application Circuit Application Power Industry Standards UL Flammability Rating UL 94V-0 Packaging Guantity 70 Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination swallable uses.		
Screw Material Steel Top Termination Type Wire Clamp Combo Head Mounting Options None Thread Size 6-32 Connector Mounting Type Cable Mount (Free Hanging) Housing Features Housing Material Thermoplastic Centerline (Pitch) 9.53 mm[.375 in] Dimensions Product Length 96.8 mm[3.811 in] Wire Size .3 – 3 mm² Operation/Application Circuit Application Power Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 70 Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Screw Head Type	Combo Phil-Slot
Top Termination Type Wire Clamp Combo Head Mounting Options None Thread Size 6-32 Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Thermoplastic Centerline (Pitch) 9.53 mm[.375 in] Dimensions Product Length 96.8 mm[3.811 in] Wire Size .3 – 3 mm² Operation/Application Circuit Application Power Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 70 Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Screw Plating Material	Zinc Chromate
Mounting Options None Thread Size 6 32 Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Thermoplastic Centerline (Pitch) 9.53 mm[.375 in] Dimensions Product Length 96.8 mm[3.811 in] Wire Size 3 - 3 mm² Operation/Application Circuit Application Power Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 70 Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Screw Material	Steel
Thread Size 6 32 Connector Mounting Type Cable Mount (Free Hanging) Housing Features Housing Material Thermoplastic Centerline (Pitch) 9.53 mm[.375 in] Dimensions Product Length 96.8 mm[3.811 in] Wire Size .3 – 3 mm? Operation/Application Circuit Application Power Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 70 Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Top Termination Type	Wire Clamp Combo Head
Connector Mounting Type Housing Features Housing Material Centerline (Pitch) Dimensions Product Length Wire Size Operation/Application Circuit Application Power Industry Standards UL Flammability Rating Packaging Features Packaging Quantity Packaging Method Other Terminal Blocks & Strips Comment Cable Mount (Free-Hanging) Thermoplastic Able Mount (Free-Hanging) Power Possami, 375 in] Possami, 375 in] Power A 96.8 mm[3.811 in] Power UL 94V-0 Packaging Features Packaging Features Packaging Guantity Do not order screw and captive clamp in combination with other top hardware.,	Mounting Options	None
Housing Features Housing Material Thermoplastic Centerline (Pitch) 9.53 mm[.375 in] Dimensions Product Length 96.8 mm[3.811 in] Wire Size .3 – 3 mm² Operation/Application Circuit Application Power Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 70 Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Thread Size	6-32
Housing Material Centerline (Pitch) 9.53 mm[.375 in] Dimensions Product Length 96.8 mm[3.811 in] Wire Size 3.3 – 3 mm² Operation/Application Circuit Application Power Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity Packaging Method Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Connector Mounting Type	Cable Mount (Free-Hanging)
Centerline (Pitch) Dimensions Product Length 96.8 mm[3.811 in] Wire Size 3 – 3 mm² Operation/Application Circuit Application Power Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 70 Packaging Method Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Housing Features	
Dimensions Product Length 96.8 mm[3.811 in] Wire Size .3 – 3 mm² Operation/Application Power Industry Standards UL 94V-0 UL Flammability Rating UL 94V-0 Packaging Features Packaging Ouantity 70 Packaging Method Package Other Do not order screw and captive clamp in combination with other top hardware.,	Housing Material	Thermoplastic
Product Length 96.8 mm[3.811 in] Wire Size .3 – 3 mm² Operation/Application Circuit Application Power Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 70 Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Centerline (Pitch)	9.53 mm[.375 in]
Wire Size Operation/Application Circuit Application Power Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity Packaging Method Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Dimensions	
Operation/Application Circuit Application Power Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Product Length	96.8 mm[3.811 in]
Circuit Application Power Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 70 Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Wire Size	$.3 - 3 \text{ mm}^2$
Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 70 Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Operation/Application	
UL Flammability Rating Packaging Features Packaging Quantity 70 Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Circuit Application	Power
Packaging Features Packaging Quantity Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Industry Standards	
Packaging Quantity Packaging Method Package Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	UL Flammability Rating	UL 94V-0
Packaging Method Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Packaging Features	
Other Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Packaging Quantity	70
Terminal Blocks & Strips Comment Do not order screw and captive clamp in combination with other top hardware.,	Packaging Method	Package
combination with other top hardware.,	Other	
consult our Product Information Center.	Terminal Blocks & Strips Comment	combination with other top hardware., Other options available upon request,

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)



	Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Buchanan 6 Series



Customers Also Bought

Barrier Strips, Tri-Barrier, Solderless Wire Wrap, Wire-to-Board, 10 Position, 9.53 mm [. 375 in] Centerline, 1 Row, Buchanan 6 Series



TE Part #5-1437652-4 TE Part #5745076-3 TE Part #5745071-1 TE Part #1825910-6 HD-20 RCPT 9P VERT FFSCRLK HD-20 PLUG 9P VERT FFSCRLK 6PCV-03-006=6PCV ASSEMBLY FSM4JH=6MM TACT SWITCH, HIGH TEMP TE Part #1-1437653-3 TE Part #8-1437653-0 TE Part #536052-5 TE Part #4-1437655-5 6PCV-08-006=6PCV ASSEMBLY 064 EURO TYPE B PIN ASSY 6PCV-16-006=6PCV ASSEMBLY 6WWV-03-008=#6 TRIBARRIER TERM TE Part #5-1437685-0 6TK2-48=SNAP TRACK

Documents

Product Drawings

6WWV-10-008=#6 TRIBARRIER TERM

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-1546159-0_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-1546159-0_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-1546159-0_L.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Barrier Strips, Tri-Barrier, Solderless Wire Wrap, Wire-to-Board, 10 Position, 9.53 mm [. 375 in] Centerline, 1 Row, Buchanan 6 Series



1-1773458-2_BARRIER_STRIPS_QUICK_REFERENCE_GUIDE

English