



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

RB400D

Features

- Small surface mounting type
- · Low reverse current and low forward voltage
- High reliability
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0

0.5 Amp Schottky Barrier Rectifier 40 Volts


Maximum Patings

Parameter	Symbol	Value	Unit
Peak Reverse Voltage	V_{RM}	40	V
DC Reverse Voltage	V_R	40	V
Mean Rectifying Current	Io	500	mA
Peak Forward Surge Current	I _{FSM}	3	А
Junction Temperature	T_J	125	°C
Storage Temperature	T _{STG}	-40 to 125	°C

Bectrical Characteristics @25°CUhless Otherwise Specified

Parameter	Symbol	Min.	Typ.	Max.	Unit
Forward Voltage @ I _F =0.5A	V _F			0.55	V
Reverse Current @V _R =30V @ V _R =10V	I _R			50 30	uA
Capacitance Between Terminals @V _R =0V, f=1MHz @V _R =10V, f=1MHz	Ст		125 20		pF

Marking: D3A



BIMENCIONO						
	INCHES		M			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.113	.117	2.87	2.97		
В	.108	.112	2.75	2.85		
С	.061	.065	1.55	1.65		
D	.036	.038	.925	.975		
E	.073	.077	1.85	1.95		
G	.0016	.0039	.04	.100		
Н	.044	.049	1.12	1.25		
J	.006	.007	.14	.17		
K	.013	.015	.34	.37		
Suggested Solder						



IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.