

6

5

4

3

2

1

PART NUMBER	ENGINEERING NO.	LENGTH ± TOLERANCE
1300500093	ENP1135M010	3' 3" +2.19"/-0" [ 1M +55.6/-0 mm ]

NOTES:

1) MATERIAL: SEE TABLE  
 2) FINISHES: SEE TABLE  
 3) CABLE: #26/8 SHIELDED TWISTED PAIR, PUR  
 4) ELECTRICAL DATA:  
 ACCORDING TO CAT5e ETHERNET STANDARD  
 MAX. VOLTAGE: 30V  
 MAX. CURRENT: 1.5A  
 5) ENVIRONMENTAL:  
 PROTECTION IP67  
 TEMPERATURE RANGE: -20°C TO +80°C  
 6) WRAP LABEL IS MARKED WITH P/N & DATE CODE.  
 7) ASSEMBLY IS RoHS COMPLIANT.

WIRE LIST

PIN #	COLOR
1	WHITE/BLUE
2	BLUE
3	WHITE/ORANGE
4	NOT USED
5	NOT USED
6	ORANGE
7	NOT USED
8	NOT USED
GND	DRAIN WIRE

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
7	1	OVERMOLD	PUR	BLACK
6	1	RJ45 PLUG	POLYCARBONATE	CLEAR
5	1	COUPLING NUT	ABS	BLACK
4	1	LABEL	PLASTIC FILM	BLACK/YELLOW
3	1	RJ45 PLUG	POLYCARBONATE	CLEAR
2	1	BOOT	PVC	BLACK
1	1	ETHERNET CABLE-CAT5E	PUR JACKET	BLACK

RELEASE DRAWING  
 EC NO: WNA2010-0432  
 DRWN: TVICKERS 2010/01/14  
 CHKD: B.WOODMA  
 APPR: DTTITUS 2010/01/15

QUALITY SYMBOLS  
 $\nabla = 0$   
 $\nabla C = 0$

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	±---	±---
3 PLACES	±---	±.005
2 PLACES	±0.13	±.010
1 PLACE	±0.25	±.020

ANGULAR ±1/2°

**DRAFT WHERE APPLICABLE  
 MUST REMAIN  
 WITHIN DIMENSIONS**

DIMENSION STYLE  
 IN

SCALE  
 1:1

DESIGN UNITS  
 INCH

THIRD ANGLE PROJECTION

DRAWN BY: --- DATE: ---  
 CHECKED BY: B.WOODMA DATE: 2010/01/14  
 APPROVED BY: DTTITUS DATE: 2010/01/15

MATERIAL NO.  
 1300500093

SIZE  
 A

TITLE  
 ETHERNET MMJ IND./RJ45  
 IO BASE T SHIELD ASSEM  
 PROPLEX STRANDED CABLE

MOLEX INCORPORATED

DOCUMENT NO.  
 SD-130050-012

SHEET NO.  
 1 OF 1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

6

5

4

3

2

1