



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Documents**

Instruction for assembly and disassembly of the connectors 23 MV-A008

**Material and plating**

**Connector parts**

Body

**Material**      **Plating**

Luranyl KR 2402      N/A

**Environmental data**

Temperature range

-65°C to +115°C

2002/95/EC (RoHS)

compliant

MR capability

non-magnetic

**Tooling**

Extraction tool for the connectors

23W100-000

**Packing**

Standard

5 pce in bag

Weight

0.25 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Herbert Babinger	27/01/09	Armin Maiwalder	02/11/11	c00	11-1011	M. Rahberger	02/11/11
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>		Page 1 / 1