

REV

PART NO

## **GENERAL SPECIFICATIONS:**

RATING: 2.5A / 250V AC

H05VV-F, 3 x 0.75 mm<sup>2</sup> CABLE TYPE / SIZE:

70° C TEMPERATURE RATING:

BLUE / BROWN / GREEN-YELLOW CONDUCTOR COLORS:

BI ACK CABLE JACKET COLOR: OVERALL LENGTH (L): 2050 ± 50 mm CABLE OUTER DIAMETER: 6.7 ± 0.1 mm

END 'A' TERMINATION: INDIA/SOUTH AFRICAN TYPE PLUG (16A), 2 POLE + GROUND

RIGHT ANGLE STYLE (BS456/IA16A3/SABS164)

END 'B' TERMINATION: IEC 320 / C5 FEMALE

APPROVALS PLUG: SABS

APPROVALS CABLE: VDE, N, S, D, FI, KEMA, SEV, CEBEC, OVE, SAA, IMMEQ

APPROVALS CONNECTOR: **ENEC-10-VDE** 

## NOTES:

Contents of this document

prior notice

1. PLUG MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBERS.



2. CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBERS.



Foot Note: Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair are subject to change without occurs. End user should consult the applicable UL,CSA or EN Standards for proper installation instruction.


Limitation of Use: Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

DASH

## **PACKING:**

**HANKING** 

 $L = 200 \pm 20 \text{ mm}$ 



RELEASED By N.Frost at 10:51 am, Sep 22, 2016

NOTES

NO.		TART NO	REV.		DESCRIPTION	NOTES
TABULATION BLOCK						
			TOLE DECIMA .xx +/- 0 .xxx +/(	).1 +/- 1°	GlobTek, Inc. www.globtek.com  186 Veterans Dr. Nort Tel. 201-784-1000 F	
INIT.BY:	DO	DATE: 08/11/10	MILLIMET .xx +/- 0. .xxx +/0	.3 +/- 1°	DWG TITLE: INDIA / SOUTH AFRICAN DETACHABLE (	CORDSET
DRAWN:	IMI.	DATE: 08/11/10	FSCN No G, CC	o.: SIZE A	MODEL: N/A	REV. C
APRVD: I	LIIVI	DATE: 08/11/10	SCALE: NONE		PART NO: 2084262M0712(R)	SHEET 1/1

DESCRIPTION