

IOA FEED-THRU-DO/NI/EX - Feed-through plug



1172189

<https://www.phoenixcontact.com/pc/products/1172189>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Non-incendive, Ex ic impeding devices for VIP I/O marshalling base elements. For limiting current (60 mA or 80 mA) and voltage (26.4 V DC) on digital outputs. For example, to control solenoid valves in the Ex area (zone 2, CID2).

Product description

Non-incendive, Ex ic impeding devices for controlling solenoid valves, alarm transmitters, or indicators installed in the Ex area. The module output limits the current to 60 mA or 80 mA (various connection terminal blocks) and a max. voltage of 26.4 V DC. The module is installed on a corresponding VIP I/O-Marshalling base element by means of plug-in contact. Installation in zone 2, "ec" type of protection is permitted.

Commercial data

Item number	1172189
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	CK8291
GTIN	4063151199012
Weight per piece (including packing)	64 g
Weight per piece (excluding packing)	64 g
Customs tariff number	85389099
Country of origin	US

IOA FEED-THRU-DO/NI/EX - Feed-through plug



1172189

<https://www.phoenixcontact.com/pc/products/1172189>

Technical data

Product properties

Product type	Interface module
Product family	VIP I/O-Marshalling

Insulation characteristics

Overvoltage category	II
Pollution degree	2

Electrical properties

Max. operating voltage U_{max}	26.4 V
Max. permissible operating voltage	26.4 V
Max. permissible current	48 mA (nA, nB)
	58.7 mA (nC, nD)

Ex data

Safety data

Input voltage U_i	26.4 V
Input current I_i	88 mA
Input power P_i	2.32 W
Max. output voltage U_o	CHn+/CHn-
Max. output current I_o	66.8 mA (nA, nB)
	89.4 mA (nC, nD)
Safety-related maximum voltage U_m	26.4 V
IIC: Max. external inductivity L_o / Max. external capacitance C_o	/ 0.25 μ F
IIB/IIIC/IIIB/IIIA: Max. external inductivity L_o / Max. external capacitance C_o	/ 1.58 μ F
IIA: Max. external inductivity L_o / Max. external capacitance C_o	/ 6.3 μ F
IIC: Max. external inductivity L_o / Max. external capacitance C_o	8.7 mH
IIB/IIIC/IIIB/IIIA: Max. external inductivity L_o / Max. external capacitance C_o	34.9 mH
IIA: Max. external inductivity L_o / Max. external capacitance C_o	69.7 mH

Dimensions

Width	10.3 mm
Height	64.2 mm
Depth	72.9 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 75 °C

IOA FEED-THRU-DO/NI/EX - Feed-through plug



1172189

<https://www.phoenixcontact.com/pc/products/1172189>

Altitude	≤ 2000 mm
Permissible humidity (operation)	0 % ... 95 % (non-condensing)

Approvals

ATEX

Identification	⊕ II 3G Ex ec IIC T4 Gc
----------------	-------------------------

IECEX

Identification	Ex ec IIC T4 Gc
	Ex ic IIC T4 Gc

UKEX

Identification	⊕ II 3G Ex ec IIC T4 Gc
----------------	-------------------------

CSA, USA/Canada

Identification	Class I, Div. 2, Groups A, B, C, D
	Ex ic IIC T4 Gc
	Ex ec IIC T4 Gc

Standards and regulations

Standards/regulations	IEC 60664
	DIN EN 50178

Mounting

Mounting type	Plug-in mounting
Assembly instructions	Plugs into VIP/...BASE...
Mounting position	any


IOA FEED-THRU-DO/NI/EX - Feed-through plug



1172189

<https://www.phoenixcontact.com/pc/products/1172189>

Drawings



1172189

<https://www.phoenixcontact.com/pc/products/1172189>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1172189>



IECEx

Approval ID: IECEx SIR 21.0005X



ATEX

Approval ID: CSANe 20ATEX3152X



CSA

Approval ID: 80047687



CSAus

Approval ID: 80047687

cCSAus

IOA FEED-THRU-DO/NI/EX - Feed-through plug



1172189

<https://www.phoenixcontact.com/pc/products/1172189>

Classifications

ECLASS

ECLASS-11.0	27141152
ECLASS-13.0	27141152
ECLASS-12.0	27141152

ETIM

ETIM 8.0	EC002780
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

IOA FEED-THRU-DO/NI/EX - Feed-through plug



1172189

<https://www.phoenixcontact.com/pc/products/1172189>

Environmental product compliance

REACH SVHC

Lead 7439-92-1

1172189

<https://www.phoenixcontact.com/pc/products/1172189>

Accessories

UC-TM 6 - Marker for terminal blocks

0818085

<https://www.phoenixcontact.com/pc/products/0818085>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

ZB 5,08:UNBEDRUCKT - Zack marker strip

0809793

<https://www.phoenixcontact.com/pc/products/0809793>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.08 mm, lettering field size: 4.98 x 10.5 mm, Number of individual labels: 10

1172189

<https://www.phoenixcontact.com/pc/products/1172189>

UC-TM 10 - Marker for terminal blocks

0818069

<https://www.phoenixcontact.com/pc/products/0818069>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 10.2 mm, lettering field size: 9.6 x 10.5 mm, Number of individual labels: 48

UC-TM 10 BU - Marker for terminal blocks

0818441

<https://www.phoenixcontact.com/pc/products/0818441>



Marker for terminal blocks, Sheet, blue, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 10.2 mm, lettering field size: 9.6 x 10.5 mm, Number of individual labels: 48

IOA FEED-THRU-DO/NI/EX - Feed-through plug

1172189

<https://www.phoenixcontact.com/pc/products/1172189>

VIP/S/MC/BASE 1-8/L/EX - Base module

2906596

<https://www.phoenixcontact.com/pc/products/2906596>



8-channel VIP I/O marshalling base element for universal use. All connections as screw connection technology. With the COMBICON connector, compatible with the Honeywell C300 and RUSIO series. Marking for channels 1–8.

VIP/S/MC/BASE 9-16/L/EX - Base module

2906630

<https://www.phoenixcontact.com/pc/products/2906630>



8-channel VIP I/O marshalling base element for universal use. All connections as screw connection technology. With the COMBICON connector, compatible with the Honeywell C300 and RUSIO series. Marking for channels 9–16.

IOA FEED-THRU-DO/NI/EX - Feed-through plug

1172189

<https://www.phoenixcontact.com/pc/products/1172189>

VIP/S/MC/BASE 17-24/L/EX - Base module

2907024

<https://www.phoenixcontact.com/pc/products/2907024>



8-channel VIP I/O marshalling base element for universal use. All connections as screw connection technology. With the COMBICON connector, compatible with the Honeywell C300 and RUSIO series. Marking for channels 17–24.

VIP/S/MC/BASE 25-32/L/EX - Base module

2907025

<https://www.phoenixcontact.com/pc/products/2907025>



8-channel VIP I/O marshalling base element for universal use. All connections as screw connection technology. With the COMBICON connector, compatible with the Honeywell C300 and RUSIO series. Marking for channels 25–32.

IOA FEED-THRU-DO/NI/EX - Feed-through plug

1172189

<https://www.phoenixcontact.com/pc/products/1172189>

VIP/S/MC/BASE 1-8/L/C/EX - Base module

2907186

<https://www.phoenixcontact.com/pc/products/2907186>



8-channel VIP I/O marshalling base element for universal use. All connections as screw connection technology. With the COMBICON connector, compatible with the Honeywell C300 and RUSIO series. Marking for channels 1–8 and painting.

VIP/S/MC/BASE 9-16/L/C/EX - Base module

2907187

<https://www.phoenixcontact.com/pc/products/2907187>



8-channel VIP I/O marshalling base element for universal use. All connections as screw connection technology. With the COMBICON connector, compatible with the Honeywell C300 and RUSIO series. Marking for channels 9–16 and painting.

IOA FEED-THRU-DO/NI/EX - Feed-through plug

1172189

<https://www.phoenixcontact.com/pc/products/1172189>

VIP/S/MC/BASE 17-24/L/C/EX - Base module

2907209

<https://www.phoenixcontact.com/pc/products/2907209>



8-channel VIP I/O marshalling base element for universal use. All connections as screw connection technology. With the COMBICON connector, compatible with the Honeywell C300 and RUSIO series. Marking for channels 17–24 and painting.

VIP/S/MC/BASE 25-32/L/C/EX - Base module

2907210

<https://www.phoenixcontact.com/pc/products/2907210>



8-channel VIP I/O marshalling base element for universal use. All connections as screw connection technology. With the COMBICON connector, compatible with the Honeywell C300 and RUSIO series. Marking for channels 25–32 and painting.

IOA FEED-THRU-DO/NI/EX - Feed-through plug



1172189

<https://www.phoenixcontact.com/pc/products/1172189>

VIP/S/D25M/BASE 1-8/L/C/EX - Base module

2906595

<https://www.phoenixcontact.com/pc/products/2906595>



8-channel VIP I/O marshalling base element for universal use. All connections as screw connection technology. This module with the D-SUB 25 connector is pin compatible with the Foxboro I/A series DCS.

VIP/MSTB/D50M/BASE/16CH/CX/EX - Base module

2908788

<https://www.phoenixcontact.com/pc/products/2908788>



16-channel VIP I/O marshalling base element for universal use. Plug-in field and supply terminals available as accessories. Either with screw or Push-in connection technology. Compatible with the Tricon CX DCS series (D-SUB 50).

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com