



PC Board Layout t=1,6mm
Component Side Show

CATEGORY 6 CHARACTERISTIC:

Frequency	Near-End dB, MIN.	Cross Talk Return Loss dB, MIN.	Attenuation dB, MAX.
1.0 MHZ	75.0	35.5	0.1
4.0 MHZ	75.0	35.5	0.1
10.0 MHZ	74.0	35.5	0.1
16.0 MHZ	69.9	35.5	0.1
25.0 MHZ	66.0	35.5	0.1
31.25 MHZ	64.1	34.1	0.1
62.5 MHZ	58.1	28.1	0.1
100.0 MHZ	54.0	24.0	0.2
200.0 MHZ	48.0	18.0	0.3
250.0 MHZ	46.0	16.0	0.3

NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125 VAC RMS.
- 2. CURRENT RATING : 1.5 AMP.
- 3. CONTACT RESISTANCE : 35 MILLIOHMS MAX.
- 4. INSULATION RESISTANCE : 1000 MEGOHMS @ 500 VDC. MIN.
- 5. DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

MECHANICAL:

- ⑧ 1. INSULATION MATERIAL : PA6T For Housing, PBT For Insert, BK, UL94V-0.
- 2. CONTACT MATERIAL : PHOSPHOR BRONZE T=0.35mm.
- 3. SHIELD MATERIAL : COPPER ALLOY T=0.20mm.
- ⑥ 4. PLATING : 50u" GOLD ON CONTACT AREA
100-200u" TIN ON SOLDER AREA
ALL OVER 30-50u" NICKEL.
- 5. OPERATING LIFE : 750 CYCLES MIN.
- 6. PCB RETENTION PRE-SOLDER : 1 LB MIN.
- 7. PCB RETENTION POST-SOLDER : 10 LBS MIN.

ENVIRONMENTAL:

- 1. STORAGE : -40°C TO +85°C
 - 2. OPERATION : 0°C TO 70°C.
 - ⑤ 3. CAT-Class : CAT6
 - ⑦ 4. WAVE SOLDERING TEMPERATURE: 255 ~ 265°C(5-10 SECONDS)
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

RoHS compliant
Unit: mm



File No.: E345352

Scale	Free	⑧	Update insulation material	27.07.2021	Luca	Date	Name
TOLERANCE		⑦	Add solder temperature	28.07.2017	Amy	Drawn	14.01.2004
.X	±0.20	⑥	Update the contact plating	25.08.2015	Amy	Approved	27.07.2021
.XX	±0.15	⑤	Update	26.06.2013	Winnie		
.XXX	±0.10	④	Add UL No	21.02.2013	Fancy		
DIM	TOL	③	Update	06.07.2009	Dean		
Angle	±5°	id.	Modification	Date	Name		

Customer-No.	
ASSMANN WSW-No.	AMJ-188-00101-CAT6

Drawing-No.	ASS 1570 CO	rev08
Replace		Sheet

