



FEMALE

A04	A05	A08	D04	B05

NOTE:

MATERIAL
 M12 INSULATOR PA66, UL94V-0, BLACK
 CABLE NUT/GROMMET/SHELL PA66, UL94V-0, BLACK
 CONTACT GOLD FLASH PLATED BRASS
 MATING NUT NICKEL PLATED BRASS

ELECTRICAL
 RATED CURRENT 2A(8P) / 4A(4/5P)
 VOLTAGE 30V(8P) / 60V(5P) / 250V(4P)
 INSULATOR RESISTANCE 100 MOhms MIN.
 CONTACT RESISTANCE 10 mOhms MAX.
 MATING CYCLES 100 CYCLES MIN

ENVIRONMENT
 OPERATION TEMPERATURE -40°C TO +85°C
 IP RATING IP66

RECOMMENDED TORQUE 0.4Nm TO 0.8Nm

858FYYY-203RBU1

SERIES _____
 858F = M12 FIELD INSTALLABLE
 CONTACT ARRANGEMENT _____
 A04 = 4P A-CODE
 A05 = 5P A-CODE
 A08 = 8P A-CODE
 D04 = 4P D-CODE
 B05 = 5P B-CODE
 GENDER _____
 2 = FEMALE
 CABLE OD _____
 B = 6mm-8mm OD
 CONTACT PLATING _____
 1 = GOLD FLASH

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: J. KADEL
 DATE: 02/04/2022

UNITS = mm

DO NOT SCALE FROM DRAWING



SCALE: NTS	SHEET 1 OF 1	REV 2
DWG NO. 858FYYY-203RBU1		