# 3/8" GOOD BUDDY® RODDER

## **FOR 2-4" CONDUIT**





Jameson offers a comprehensive Good Buddy® family to meet various applications for 3/8" rod:

Manhole-to-riser, riser-to-riser, cable vaults and large conduit runs.

- Recommended For Use In 2-4" Conduit
- .250 Core 3/8 OD Rod
- 7" Bending Radius
- 1,000-lb Tensile/Pull Strength
- · Accessory Kit, End Ferrule and Pulling Eye Included









GOOD BUDDY®II

400' - 600'



GOOD BUDDY®III

300' - 400'



### **ACCESSORY KIT**

Contents: Canvas Pouch, Swivel Pulling Eye, Splice Ferrule, End Ferrule, Adhesive, and Emery Cloth. Pouch attaches to Rodder Frame for Easy Access (Included With Rodder)

Part Number	Good Buddy® Rodders
9-25-300M	300' X 3/8" Good Buddy
9-25-400M	400' X 3/8" Good Buddy
11A-25-400M	400' X 3/8" Good Buddy II
11A-25-500M	500' X 3/8" Good Buddy II
11A-25-600M	600' X 3/8" Good Buddy II
9A-25-300M	300' X 3/8" Good Buddy III
9A-25-400M	400' X 3/8" Good Buddy III

All Good Buddy® conduit rodder models come standard with rod marked in 5' increments. Add 'MM' to part number for metric measure (1m increments).

## 3/8" RODDERS







#### GOOD BUDDY®

#### Detach or Fold Frame For Transport Into Confined Areas

- 300' and 400' lengths
- Folds to 10" width for carrying into manholes
- Reel can be detached from frame
- Frame handle for easy transport
- · Friction brake and safety roller feed
- · Operates vertically or horizontally

29"H x 29"L x 27"W (Folds to 10" Width)





### **GOOD BUDDY®II**

#### Increased Rod Length For Longer Runs

- 400', 500' and 600' lengths
- Oversized wheels support weight of longer rod
- · Frame handle and wheels for transport
- · Friction brake and safety roller feed
- Operates vertically or horizontally 39"H x 32"L x 18"W





## GOOD BUDDY®III

#### **Smaller Frame For Maximum Portability**

- 300' and 400' lengths
- Wheels and frame handle for transport
- Smaller frame size than GB or GB II
- Friction brake and safety roller feed
- Operates vertically or horizontally 34"H x 26.5"L x 15.5"W







All Terrain Wheel

#### Part Accessories Thread 3/8" - 16 UNC Number 9-25-AK Accessory Kit End Ferrule, Splice Ferrule, Adhesive, Emery Cloth, Pouch 9-139 Swivel Eye Attach pull line or grip to freely rotating eye 9-141 Roller Guide Guides rod through bends, sweeps, misalignments, wires Use with Swivel Eye for larger pulling loop to attach Pulling 11-142 Shackle Fitting Eye. Must use 11-139 Swivel Eye. Connect two rods when single length is not long enough; 9-143 Swivel Coupling provides rotation when pulling line, wire or rope. 9-148 **Rod Grapples** Connects two rodders from opposite directions 9-25-12ST 12" Stinger Tip Guide rod through bends, sweeps, misalignments 9-25-24ST 24" Stinger Tip 9-140 Splice Repair Kit Splice Ferrule, Adhesive, Emery Cloth, Instructions 9-146 End Ferrule Repair End Ferrule, Adhesive, Emery Cloth, Instructions 11A-AWK AT Wheel Kit Replacement All-Terrain Wheel Kit for Good Buddy II only

## **ACCESSORIES**

Sold Separately

Roller Guide

Swivel Eye

End Ferrule