



PCE Americas Inc.
 711 Commerce Way
 Suite 8
 Jupiter
 FL-33458
 USA
 From outside US: +1
 Tel: (561) 320-9162
 Fax: (561) 320-9176
 info@pce-americas.com

PCE Instruments UK Ltd.
 Units 12/13
 Southpoint Business Park
 Ensign way
 Hampshire / Southampton
 United Kingdom, SO31 4RF
 From outside UK: +44
 Tel: (0) 2380 98703 0
 Fax: (0) 2380 98703 9
 info@pce-instruments.com

www.pce-instruments.com/english
www.pce-instruments.com

Technical Gloss Meter PCE-PGM 100

**Gloss meter for mobile use / flexibility due to various measuring geometries /
 3.5 " TFT display / very short measuring time / internal memory for readings /
 including evaluation software**

The PCE-PGM 100 gloss meter works with measuring geometries of 20 °, 60 ° and 85 °, using the reflection principle. This means that the gloss meter emits light which hits the surface to be tested. A part of the light will be absorbed by the surface and another part will be reflected. After this, the gloss meter will calculate the degree of gloss.

The wide measurement range allows the user to test many different surfaces. These features make the gloss degree meter very useful for gloss measurements in quality and incoming goods control. The included software makes later evaluation of the measured data easily possible.

- Various measuring geometries
- 3.5 "TFT
- Internal measurement value storage
- Calibration plate included in the delivery content
- short measuring time
- Evaluation software

Technical Data

Measurement geometry	20 ° / 60 ° / 85 °
Display	3.5 " TFT touch display
Standards	ISO 2813 GB/T 9754 ASTM D 523 ASTM D 2457
Measuring surface	20 ° : 10 x 10 mm 60 ° : 9 x 15 mm 85 ° : 5 x 36 mm
Measuring range	20 ° : 0 ... 1000 GU 60 ° : 0 ... 1000 GU 85 ° : 0 ... 160 GU
Readability	0.1 GU

Repeatability	Meas. range 0 ... 10 GU: ± 0.1 GU Meas. range 10 ... 100 GU: ± 0.2 GU Meas. range 100 ... 1000 GU: ± 0.2 GU (%)
Reproducibility	Meas. range 0 ... 10 GU: ± 0.2 GU Meas. range 10 ... 100 GU: ± 0.5 GU Meas. range 100 ... 1000 GU: ± 0.5 GU (%)
Chromaticity	Fulfils CIE 1931(2 °) under a CIE C – light source
Measurement accuracy	$\pm 1.5 / \pm 1.5$ %
Measuring time	0.1 second
Dimensions	160 x 75 x 90 mm
Weight	350 g
Menu language	English, Chinese
Power supply	3200 mAh Li-ion rechargeable battery
Interface	USB / RS-232
Measuring storage	Baseline measurement:1000
Operating temperature	0 ... +40 °C
Storage temperature	-20 ... +50 °C
Relative humidity	<85% rel. humidity (non-condensing)

Delivery Contents

- 1 x gloss level meter PCE-PGM 100
- 1 x charging adaptor
- 1 x rechargeable lithium-ion battery
- 1 x USB cable
- 1 x calibration plate
- 1 x evaluation software (on a CD-ROM)
- 1 x instruction manual