
	THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1								
REV	REV DESCRIPTION DATE BY								
Α	INITIAL RELEASE 10/28/22 YA								



Dwg. Number	Customer P/N	Times P/N	Length(L) in 'inch'
IE-00416-01	-	IBPS092-KMKM-6.0IN	6 +0.20/-0
IE-00416-02	-	IBPS092-KMKM-8.0IN	8 +0.20/-0
IE-00416-03	-	IBPS092-KMKM-10.0IN	10 +0.20/-0
IE-00416-04	-	IBPS092-KMKM-12.0IN	12 +0.24/-0

### 1.0 Scope

This drawing documents the construction and performance of PT- 092 cable assemblies manufactured by Times Microwave systems.

#### 2.0 Cable Information

- 2.1 Cable to be PT-092
- 2.2 Jacket color to be Black
- 2.3 Jacket material to be Tefzel
- 2.4 Nominal cable impedance to be 50 ohms
- 2.5 Cable diameter to be 0.101" [2.57mm] (Nominal).

### 3.0 Connector Information

3.1 Forward Connector

Type K (M) Straight Connector (SP116)

Connector Body - Stainless Steel, Gold Plated

Center Contact - Beryllium Copper, Gold Plated

# 3.2 After Connector

Type K (M) Straight Connector (SP116)

Connector Body - Stainless Steel, Gold Plated

Center Contact - Beryllium Copper, Gold Plated

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when specified.	Aŗ	oprova	als	_		TIMES	MICROW	VAVE SYSTEMS	
	Drawn	YA	10/28/22		II		www.timesmicrowave.com		
These drawings and specifications contain proprietary information	Checked			PT-092 CABLE ASSEMBLY					
which is the property of	Approved			]	(Space Assemblies)				
Times Microwave	Approved	pproved		Size	e CAGE CODE		Drawing No.:		
Systems.				Α	6899	99	IE.	-00416-XX	
				Scale:	NA	Rev.	(A)	Sheet: 1 of 3	

	THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1								
REV	REV DESCRIPTION DATE BY								
Α	INITIAL RELEASE 10/28/22 YA								

### 4.0 Electrical Performance

- 4.1 Frequency range: DC 40GHz
- 4.2 Insertion loss & VSWR: As per below table,

Dwg. Number	Max. Insertion Loss in dB	Max. VSWR
Dwg. Number	@ 40GHz	@ 40GHz
IE-00416-01	1.34	1.40
IE-00416-02	1.63	1.40
IE-00416-03	1.93	1.40
IE-00416-04	2.23	1.40

#### 5.0 Mechanical Performance

- 5.1 Overall Length to be specified length.
- 5.2 Minimum Bend radius is 0.437" [11.1mm].

# 6.0 Environmental Performance

- 6.1 Installation Temperature Range (-65°C to +150°C)
- 6.2 Storage Temperature Range (-65°C to +150°C)
- 6.3 Operating Temperature Range (-65°C to +150°C)

### 7.0 Marking

- 7.1 Markers are to be black text on White Color Marker Sleeve.
- 7.2 Marker Configuration to be:

Dwg. Number	Marker 1				
IE-00416-01	Times Microwave Systems IBPS092-KMKM-6.0IN \$\$\$\$\$				
IE-00416-02	Times Microwave Systems IBPS092-KMKM-8.0IN \$\$\$\$\$				
IE-00416-03	Times Microwave Systems IBPS092-KMKM-10.0IN \$\$\$\$\$				

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when spec-	l	prova	als	_		TIMES	MICROW	VAVE SYSTEMS
ified.	Drawn	YA	10/28/22			www.timesmicrowave.com		
These drawings and specifications contain proprietary information	Checked			PT-092 CABLE ASSEMBLY				
which is the property of	Approved				(Space Assemblies)			
i imes iviicrowave	Approved			Size	CAGE CODE <b>68999</b>		Drawing No.:	
Systems.				A			IE.	IE-00416-XX
				Scale:	NA	Rev.	(A)	Sheet: 2 of 3

	THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1								
REV DESCRIPTION DATE BY									
Α	INITIAL RELEASE 10/28/22 YA								

IE-00416-04	Times Microwave Systems IBPS092-KMKM-12.0IN \$\$\$\$\$
	\$\$\$\$\$

- 7.3 \$ = 5-digit Serial Number for this specific configuration.
- 7.4 Register to be Maintained for Serial Number.

# 8.0 NOTES

- 8.1 All Dimensions are in INCH.
- 8.2 Assemblies built in Class 100,000 clean room.
- 8.3 Low outgassing materials per ASTM E595.
- 8.4 Unless Otherwise Specified: Tolerance will be,

Linear Dimension	Tolerance
<20 INCH	±0.4 INCH
20-79 INCH	±0.6 INCH
>79 INCH	±0.8 INCH

<sup>\*\*</sup>Tolerances are not accumulative.

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when spec-	Approvals			TIMES MICROWAVE SYSTEMS				/AVE SYSTEMS	
ified.	Drawn	YA	10/28/22		www.timesmicrowave.com			crowave.com	
These drawings and specifications contain proprietary information	Checked			PT-092 CABLE ASSEMBLY					
which is the property of	Annroyed				(Space Assemblies)				
Times Microwave	Approved			Size	CAGE CODE <b>68999</b>		Drawing No.: IE-00416-XX		
Systems.				Α					
				Scale:	NA	Rev. (	(A)	Sheet: 3 of 3	