## Scotch<sup>®</sup> Transparent Label Protection Tape 356

Product Description	Scotch <sup>®</sup> Label Protection Tape 356 is a transparent, tough film tape made especia for label protection in outdoor applications or where the application demands ext resistance to moisture, chemicals, or abrasion. The long-aging transparent adhesi holds fast to most packages and containers and is water and chemical resistant.		
Construction	Backing	Adhesive	Colors
Construction	Dacking		
Construction	3M <sup>™</sup> Scotchpar <sup>™</sup> polyester film	Acrylic	Transparent
Construction Typical Physical Properties	3M <sup>™</sup> Scotchpar <sup>™</sup> polyester film Note: The following technical in	Acrylic formation and data should be considere I not be used for specification purposes.	
Typical Physical	3M <sup>™</sup> Scotchpar <sup>™</sup> polyester film Note: The following technical in	formation and data should be considere I not be used for specification purposes.	
Typical Physical	3M <sup>™</sup> Scotchpar <sup>™</sup> polyester film Note: The following technical in	formation and data should be considere I not be used for specification purposes.	d representativ
Typical Physical	<ul> <li>3M<sup>™</sup> Scotchpar<sup>™</sup> polyester film</li> <li>Note: The following technical in or typical only, and should</li> <li>Adhesion to Steel:</li> <li>Tensile Strength:</li> </ul>	formation and data should be considere I not be used for specification purposes. AS	d representativ
Typical Physical	3M <sup>™</sup> Scotchpar <sup>™</sup> polyester film Note: The following technical in or typical only, and should Adhesion to Steel:	formation and data should be considere I not be used for specification purposes. AS 20 oz./in. width (22 N/100 mm width)	d representativ STM Test Metho D-3330

Features

• Strong, and abrasion resistant.

- Water and chemical resistant.
- Long aging.
- Makes the best laminate choice for outdoor application.
- Helps prevent packing lists from being scuffed off.
- Guards information from damage from chemicals and water.
- Enhances clarity and sharpness of bar codes.
- Helps prevent labels from yellowing or drying out during normal label life.
- Holds tight to most cartons and containers.

## **3M**

## **Scotch<sup>®</sup> Transparent Label Protection Tape** 356

Available Sizes	Standard Widths:	2 in., 3 in., 4 in., 6 in.	
	Available by Special Order:	Custom widths and lengths available on request, subject to minimum order requirements.	
	Core Size (ID):	3 in.	
	Lengths:	72 yds., bulk only	
Application Techniques	A line of in-stock dispensers including M707, M727, M797 is available to facilitate the use of Scotch <sup>®</sup> Label Protection Tape 356.		
Storage Conditions	Storage of Scotch <sup>®</sup> Tape 356 at 70°F (21°C) and 40-50% relative humidity is recommended.		
Product Use	All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.		
Warranty and Limited Remedy	Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.		
Limitation of Liability	Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.		
	This Industrial Adhesives and Tapes Divisior	ISO 9001:2000	



Industrial Business Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue St. Paul, MN 55144-1000 800-362-3550 • 877-369-2923 (fax) www.3M.com/industrial



Recycled Paper 40% pre-consumer 10% post-consumer