



ISO9001:2008 Certified

Mechanical Specifications (mm)

	D:	22.0	± max
	T:	5.0	± max
	Lead Diameter	1.0	± nom
	S:	7.8	± nom
	L:	38.0	± nom
	Coating Lead Run Down (straight Leads)	5.0	± max
	B:	11.50	± nom
	C:	4.33	± nom



Electrical Specifications

	Resistance:	120. (Ω	± 25 %
Max Steady State Current upto 65°C:	2.00	A	
Max Rec. Energy Rating:	80	J	
Actual Failure Instantaneous Energy:	170	J	
Maximum Capacitance @ 120 VAC:	5,557	µf	
Maximum Capacitance @ 240 VAC:	1,389	µf	
Resistance @ 100% Max Current:		Ω	
Resistance @ 50% Max Current:	3.70	Ω	
Body Temperature at 100% Max Current:		°c	
Dissipation Constant:	32.4	mw/°c	
Thermal Time Constant:	94	Sec.	
Material Type (for Beta and Curve):	L		

SL22 12102	
Date: 11/11/2008	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: a