

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	OPERATING&STORAGE HUMIDITY RANGE	85 % MAX	APPLICABLE CABLE	CABLE DIAMETER : φ8.8±0.5	
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
△					
REMARK			APPROVED	A0. SUZUKI	09. 10. 05
			CHECKED	KN. ICHIKAWA	09. 10. 02
			DESIGNED	TU. TANI GUCHI	09. 10. 02
			DRAWN	TU. TANI GUCHI	09. 10. 02
Unless otherwise specified, refer to JIS C 5402.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-126659-00		
HRS		SPECIFICATION SHEET		DH-37-CMB (8. 8)	
		HIROSE ELECTRIC CO., LTD.			
	PART NO.	CODE NO.	CL244-0033-0-00	△	1/