

CUC-USB3.1-J1ST-AH/UCF-SMD/THR - USB PCB connectors



1332643

<https://www.phoenixcontact.com/us/products/1332643>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

USB PCB connectors, degree of protection: IP20, number of positions: 24, 10 Gbps, material: Metal, connection method: Solder connection, cable outlet: straight, USB 3.0



Your advantages

- Optimized for SMD/THR reflow soldering processes
- Data transmission up to 10 Gbps
- Can be processed automatically thanks to tape-on-reel packaging

Commercial data

Item number	1332643
Packing unit	1 pc
Minimum order quantity	800 pc
Sales key	AB14
Product key	ABNDAC
GTIN	4063151630249
Weight per piece (including packing)	1.095 g
Weight per piece (excluding packing)	1 g
Customs tariff number	85366930
Country of origin	CN

CUC-USB3.1-J1ST-AH/UCF-SMD/THR - USB PCB connectors



1332643

<https://www.phoenixcontact.com/us/products/1332643>

Technical data

Product properties

Type	USB-C
Product type	Data connector (device side)
Sensor type	USB 3.0
Number of positions	24
Type of packaging	Tape and Reel
[W] tape width	24.00 mm
[A] coil diameter	330.00 mm
Connection profile	USB-C
Number of slots	1
Type	Socket
Shielded	yes
Cable outlet	straight

Insulation characteristics

Overvoltage category	I
Degree of pollution	2

Electrical properties

Rated voltage (III/2)	20 V
Rated surge voltage (III/2)	1500 V
Rated current	5 A
Contact resistance	40 mΩ
Frequency range	10 Hz ... 55 Hz
Insulation resistance	100 MΩ
Transmission medium	Copper
Transmission characteristics (category)	USB 3.2 Gen 2
Transmission speed	10 Gbps
Power transmission	100 W

Connection data

Connection technology

Connection method	Solder connection
-------------------	-------------------

Dimensions

Width	9.85 mm
Height	3.31 mm
Length	9.87 mm
Orientation to	90.00 °

CUC-USB3.1-J1ST-AH/UCF-SMD/THR - USB PCB connectors



1332643

<https://www.phoenixcontact.com/us/products/1332643>

Material specifications

Color of the housing part	black
Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Gold over nickel
Contact carrier material	LCP
Housing material	Metal

Cable/line

Test voltage Core/Core	100 V
Test voltage Core/Shield	100 V
Acceleration	3.1 m/s ²
Halogen-free	yes

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 10000
Insertion force per signal contact	20.00 N
Extraction force per signal contact	< 8 N

Environmental and real-life conditions

Test specification

Specification	EIA 364-1000
Frequency	10-55 Hz
Sweep speed	1 octave/min
Amplitude	1.52 mm
Test duration	2 h
Contact resistance R ₁	40 mΩ

Test specification

Specification	60068-2-27
Acceleration	50 g
Number of shocks per direction	18

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 85 °C

Mounting

Mounting type	THR soldering
Connection method	Solder connection

Processing notes

CUC-USB3.1-J1ST-AH/UCF-SMD/THR - USB PCB connectors



1332643

<https://www.phoenixcontact.com/us/products/1332643>

Process	THR/SMD
Moisture Sensitive Level	MSL 1
Classification temperature T _c	260 °C
Solder cycles in the reflow	3

CUC-USB3.1-J1ST-AH/UCF-SMD/THR - USB PCB connectors



1332643

<https://www.phoenixcontact.com/us/products/1332643>

Classifications

ECLASS

ECLASS-11.0	27440390
ECLASS-12.0	27440390
ECLASS-13.0	27440390

ETIM

ETIM 8.0	EC001121
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

CUC-USB3.1-J1ST-AH/UCF-SMD/THR - USB PCB connectors



1332643

<https://www.phoenixcontact.com/us/products/1332643>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com