

Termination board - IBS PCI RI-LK - 2704045

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Termination board, with FO connection and external power supply

Product Features

- External 24 V DC power supply
- Direct integration into OPC-based visualization systems via OPC server
- Installation of several cards in a PC with monitoring of multiple INTERBUS lines
- INTERBUS parameter channel (PCP) supported
- Access to INTERBUS system data and controller data via visualization stations
- Compatible driver
- Parameterization and diagnostics with Diag+
- Access to high-level language applications via HFI



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	235.9 GRM
Custom tariff number	85423190
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---------------------------------------------------------------------------

Dimensions

Width	134 mm
Height	107 mm

Termination board - IBS PCI RI-LK - 2704045

Technical data

Dimensions

Depth	20 mm
-------	-------

Ambient conditions

Degree of protection	IP00
Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	95 % (non-condensing)
Permissible humidity (storage/transport)	95 % (non-condensing)

Control system

Control system	IBM-compatible PCs with PCI slot
Configuration tool	Own configurator on CD

Software interfaces

Software driver	Windows NT
	Windows 2000
	Windows XP
Application interface	DDI
	OPC-DA server

Software requirements

Configuration tool	Own configurator on CD
--------------------	------------------------

Power supply

Power supply connection	Via PCI bus or 2-pos. MINI-COMBICON
Typical current consumption	1 A
Supply voltage	3.3 V DC (internal)
	5 V DC (internal)
	24 V DC (external)
Supply voltage range	18 V DC ... 30 V DC

General

Weight	130 g
Format	Short plug-in card, 1-slot

Data interfaces

Interface	INTERBUS remote bus, incoming
Connection method	FSMA plugs
Transmission speed	500 kBit/s / 2MBit/s (can be switched)
Interface	INTERBUS remote bus, outgoing
Connection method	FSMA plugs

Termination board - IBS PCI RI-LK - 2704045

Technical data

Data interfaces

Transmission speed	500 kBit/s / 2MBit/s (can be switched)
Interface	Host system
Connection method	PCI slot in acc. with PCI specification 2.1 or higher, PCI bus, 32 bits, 33 MHz, 3.3/5 V
Interface	External power supply
Connection method	2-pos. MINI-COMBICON male connector
Interrupts	1 IRQ, PNP

Direct I/Os

Number of pulse direction outputs	0
Limit frequency	0 kHz
Number of inputs	0
Input frequency	0 kHz

Fieldbus function

Amount of process data	max. 8192 Byte (INTERBUS-Master)
	256 Bit (INTERBUS-Slave)
Number of parameter data	4 Byte
Number of supported devices	max. 512 (of which 254 are remote bus devices/bus segments)
Number of devices with parameter channel	max. 126
Module classification	INTERBUS-Slave

Classifications

eCl@ss

eCl@ss 4.0	27240603
eCl@ss 4.1	27240603
eCl@ss 5.0	27242208
eCl@ss 5.1	27242208
eCl@ss 6.0	27242208
eCl@ss 7.0	27242208
eCl@ss 8.0	27242208

ETIM

ETIM 2.0	EC001425
ETIM 3.0	EC001425
ETIM 4.0	EC000236
ETIM 5.0	EC000236

Termination board - IBS PCI RI-LK - 2704045

Classifications

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals


UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized 

cUL Recognized 

cULus Recognized 