# **Data sheet** 2765.2 AQI 2/95 YE





External insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 44.86 mm, Rated current: 232 A; Colour: Yellow

**RAL:** 1026

## **Business data**

Article number	<u>2765.2</u>
Article name	AQI 2/95 YE
GTIN (EAN)	4044211054953
Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	93 g
Weight per piece (including packaging)	93.4 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	2765.2
Product description	External insulated cross-connector

# **Data sheet**





44.86 mm	
25 mm	
1000 V	
1000 V	
232 A	
3	
2	
Copper	
Tin-plated	
Polyamide 6.6	
V-2	
-40 °C	
105 °C	
Plug in	
✓	
✓	
2	
Yes	
No	
Yes	
	25 mm  1000 V  1000 V  232 A  3  2  Copper Tin-plated Polyamide 6.6 V-2 -40 °C 105 °C  Plug in  ✓  ✓  2  Yes No

## Data sheet 2765.2 AQI 2/95 YE



Media

## **Data sheet**

## 2765.2 AQI 2/95 YE



### **Accessories**

#### ##INVERSE##CONTA-CONNECT



Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 95 mm², Width: 25 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1122.2	RK 95 BG	4044211018979	10



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 95 mm², Width: 25 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1583.2	RK 95-D BG	4044211047726	10



Ex feed-through terminal ATEX-certified, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 95 mm², Width: 25 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1476.2	RK 95 Ex BG	4044211107918	10