



General ordering data

| | |
|------------------|---|
| Order No. | 0468260051 |
| Part designation | DEK 6,5 FS 51-100 |
| Version | Connector markers, L x W: 5 x 6.5 mm, Polyamide, white |
| EAN | 4008190162900 |
| Qty. | 500 pc(s). |

Markings

| | |
|--|-------------------|
| Cadmium | no |
| Can be labelled with thermal transfer printers | No |
| Can be printed with plotter | No |
| Can be written with dot-matrix printer | No |
| Can be written with laser printer | No |
| Colour of printing | black |
| Function | Connector markers |
| Halogen | no |
| Length | 5 mm |
| Material | Polyamide |
| Material colour | white |
| Material colour according to resistance code | 9 |
| Max. temperature, continuous | 100 °C |
| Min. temperature, continuous | -40 °C |
| Orientation of print | vertical |
| Pin can be written (STI) | No |
| Pitch | 6.5 mm |
| PrintJet | No |
| Printed characters | Numbers |
| Printing method | MC Laser |
| Silicone | no |
| Speed marking laser | No |
| Type of printing | Standard |
| UL 94 flammability class | V2 |
| Width | 6.5 mm |

Classifications

| | |
|------------|-------------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| eClass 4.1 | 24-19-02-19 |
| eClass 5.0 | 27-14-11-37 |
| eClass 5.1 | 27-14-11-37 |

Similar products

| Order No. | Part designation | Version |
|------------|--------------------|--|
| 0468260001 | DEK 6,5 FS 1-50 | Connector markers, L x W: 5 x 6.5 mm, Polyamide, white |
| 0468260101 | DEK 6,5 FS 101-150 | Connector markers, L x W: 5 x 6.5 mm, Polyamide, white |