



# RUGGED KEYBOARD

Designed for Public Safety  
and Mobile Data  
Applications

## SPECIFICATIONS

- Storage Temperature: -55C to +85C
- Operating Temperature: -40C to +70C
- Operating Humidity: 100%
- Dimensions: 12.00 x 7.75 x 1.25 in (340.85 x 196.85 x 31.75 mm)
- Weight: 2 lbs

## COMPLIANT

- FCC
- CE
- RoHS

## FEATURES

- 83 Keys
- Rubber
- Red Backlighting Rated For Life of the Product (200,000 hr LED's)
- Low Cost, Ultra Rugged Keyboard
- Low Profile With Ergonomic Design and Feel
- Tactile Full Travel Key Switches
- Embedded Multi-Media Functionality
- Chemical Resistant Engineered Plastic Resin Housing and Keycaps
- Sealed Product to Prevent Water Intrusion (Mil Std 810 Compliant)
- Splash-Proof Touchpad With 2 Sealed Mouse Buttons
- 10 Million Actuations Per Key
- Optional Logo
- Multiple Standard Mounting Options
- Non-Rubber Option Available

## ELECTRICAL SPECIFICATIONS

- Voltage: +5Vdc From Data Cord
- Radiated Immunity: 20 Volts / Meter
- Backlight Dimming Includes 8 Levels of Intensity Controlled by "Fn" + "0" - "7" Keys or "Fn" Up / Down" Cursor Keys
- X/Y Position Resolution: 500 Points / Inch (20 Points Max)

## INTERFACE

USB

TG3 PART NUMBER	DESCRIPTION
KBA-BLTXR-USNNR-US	Black, Rubber, USB, Straight Cord, Red Backlight
KBA-BLTXR-UCNNR-US	Black, Rubber, USB, Coiled Cord, Red Backlight