## **HellermannTyton**

## **Specification Sheet**

Part Number: 166-90132

External NPT thread provides a secure connection. Twist-on installation makes future access fast and easy.

Internal spigot design helps ease threading of fitting onto conduit.

All-around "teeth" attach firmly to conduit and deliver a high extraction force.

Durable nylon material has high resistance to salts, oils, weak acids and solvents.

IP65 rating for protection against wind, dirt and low pressure jets of water from all directions.

HelaGuard Non-Metallic IP65 Fitting, 90-Elbow, NPT Thread, 1.25" Dia, PA66, Black, 2/pkg

Article Number	166-90132
Туре	PSR125-90-1250
Color	Black (BK)
Quantity Per	bag
Product Description	Compression fittings feature a twist-on design for easy installation and future access. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Fits HelaGuard non-metallic conduits and tubing.



Short Description	HelaGuard Non-Metallic IP65 Fitting, 90-Elbow, NPT Thread, 1.25" Dia, PA66, Black, 2/pkg		
Global Part Name	PSR125-90-1250-PA66-BK		
Length L (Imperial)	4.45		
Length L (Metric)	113		
Variant	90° Elbow		
Outside Diameter OD (Imperial)	2.36		
Outside Diameter OD (Metric)	60		
Nominal Diameter (Imperial)	1.25		
Nominal Diameter (Metric)	40		
Material	Polyamide 6.6 (PA66)		
Material Shortcut	PA66		
Flammability	UL 94 V-2		
Halogen Free	Yes		
UV Resistant (Yes/No)	No		

Operating Temperature	-40°F to +248°F
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	2
Package Quantity (Metric)	2
Customs Number	3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

(-40°C to +120°C)

© 2023 HellermannTyton. All Rights Reserved.

Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions
------------	----------------------	------------	----------------------