


	REVISIONS					
REV	ECO	DESCRIPTION	DATE	BY	APPR	
A1	-	RELEASE NEW DRAWING	17/OCT/18	BROOK	TOMMY	
A2	_	ADD MORE MATERIAL NOTES	24/OCT/18	ROOKIE	TOMMY	



RECPT, 18 SZ 20 PIN, RD, WIDE THD

AHDM04-18-20PR

⋧

ITEM

SHEET 1 OF 1

NOTES: UNLESS OTHERWISE SPECIFIED


1. MATERIAL:

SHELL: ZINC ALLOY, NICKEL PLATED INSERT AND RETAINING RING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: THREADED HOUSING; REDUCED DIA. SEAL
- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25℃.
 - 3.4 MOISTURE RESISTANCE: IP67&IP69K (MATED CONDITION).
 - 3.5 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDM06-18-20S* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.


6. CONTACT SIZE AND WIRE RANGE:

CONTACT SIZE	MIN. INSUL O.D.	MAX. INSUL O.D.	TYPICAL WIRE RANGE	CURRENT RATING
20	1.02 mm (.040 in)	2.41 mm (.095 in)	16-22 AWG	7.5 AMPS
16	1.35 mm (.053 in)	3.05 mm (.120 in)	14-20 AWG	13 AMPS



RECOMMENDED PANEL MOUNTING HOLE

RECOMMENDED PANEL THICKNESS:1.6 TO 4.7MM



	AHDM0	4-18-20F	PR					
	PART NUMBER			DESCRIPTION				
QUANTITY		- 1	MAT	ERI	AL:	SLI	ST	
UNLESS OTHER	WISE SPECIFIED	SIGN	IATURES	DATE		Λ	mphono	
2) Tolerances are a 1 PL DEC ±0.30		DRAWN:	ROOKIE	24/OCT/18]		mpheno	ı
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	ORION	24/OCT/18	_	Sin	e Systems - www.amphenol-sine.com	
3) Note reference	- <u></u>	ENGINEER:]		44724 Morley Drive	
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	24/OCT/18	 		Clinton Township, MI 48036	
		CUSTOMER:			1	RECPT	. 18 SZ 20 PIN. RD. WIDE -	THD
PROCESS SPECIFICA	TIONS:	INFORMATION SPECIFICATION SHOWN HERE THE AMPHENIOF REPRODU	G IS SUPPLIED I I ONLY. DESIGN INS AND PERFO ON ARE THE PF OL CORPORATI CTION ARE IMP ARE SUBJECT T	I FEATURES, DRMANCE DATA ROPERTY OF ON. NO RIGHTS LIED. ALL O NORMAI	size B	C-	AHDM04-18-20PR	REV
NEXT ASS'Y:		MANUFACTUR	RING VARIATION	IS.	SCALE:	NONE	SHEET 1	OF

ATM Series™ - Contact Size 20 Options

Machined Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Туре	
AT60-010-2031	Male Contact - Pin, Gold-plated	20	16-18	Machined	
AT62-005-20141	Female Contact - Socket, Gold-plated	20	16-18	Machined	
AT60-010-20141	Male Contact - Pin, Nickel-plated	20	16-18	Machined	
AT62-005-2031	Female Contact - Socket, Nickel-plated	20	16-18	Machined	
AT60-202-2031	Male Contact - Pin, Gold-plated	20	20-22	Machined	
AT62-201-2031	Female Contact - Socket, Gold-plated	20	20-22	Machined	
AT60-202-20141	Male Contact - Pin, Nickel-plated	20	20-22	Machined	
AT62-201-20141	Female Contact - Socket, Nickel-plated	20	20-22	Machined	

	Tooling - Machined Contacts					
Part	Part Number	Description				
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)				
5	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)				

	Contact Removal Tools					
Part	Part Number	Description				
	ATRT-100	Used for removal of contacts for A Series™ products				
	AT11-240-2005	Contact Removal Tool, Plastic, Size 20				
	AT13-204-2005	Sealing Plug, Size 20, White				

Stamped & Formed Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Туре		
AT60-20-0144	Male Contact - Pin, Gold-plated	20	16-22	Stamped & Formed		
AT62-20-0144	Female Contact - Socket, Gold-plated	20	16-22	Stamped & Formed		
AT60-20-0244	Male Contact - Socket, Gold-plated	20	16-22	Stamped & Formed		
AT62-20-0244	Female Contact - Socket, Gold-plated	20	16-22	Stamped & Formed		
AT60-20-0122	Male Contact - Pin, Nickel-plated	20	16-22	Stamped & Formed		
AT62-20-0122	Female Contact - Socket, Nickel-plated	20	16-22	Stamped & Formed		
AT60-20-0222	Male Contact - Socket, Nickel-plated	20	16-22	Stamped & Formed		
AT62-20-0222	Female Contact - Socket, Nickel-plated	20	16-22	Stamped & Formed		
AT60-20-0277	Male Contact - Socket, Tin-plated	20	16-22	Stamped & Formed		
AT62-20-0277	Female Contact - Socket, Tin-plated	20	16-22	Stamped & Formed		
AT60-20-0422	Male Contact - Socket, Nickel-plated	20	20-22	Stamped & Formed		
AT62-20-0444	Female Contact - Socket, Gold-plated	20	20-22	Stamped & Formed		

Tooling - Stamped & Formed Contacts					
Part	Part Number	Description			
	MFX-3974	Crimp Die - Size 20 (S&F contacts only)			
	MFX-3976	Crimp Die - Size 20 (S&F contacts only) 20-22AWG -04XX Series			
W.	MFX-3978	Crimp Die - Size 20 (S&F contacts only) 20-22AWG -02XX Series			
K	АТТ-20-00	Hand Crimp Tool - Size 20, 20AWG (S&F contacts only)			

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

AT Series™ - Contact Size 16 Options

Machined Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Туре	
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined	
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined	
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined	
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined	
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined	
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined	
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined	
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined	
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined	
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined	
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined	
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined	

	Tooling - Machined Contacts				
Part	Part Number	Description			
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)			
5	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)			

	Contact Removal Tools						
Part	Part Number	Description					
	ATRT-100	Used for removal of contacts for A Series™ products					
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16					
4	A114017	Sealing Plug, Size 16, White					

Stamped & Formed Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Туре		
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed		
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed		
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed		
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed		
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed		
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed		
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed		
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed		
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed		
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed		
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed		
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed		
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed		
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed		
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed		
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed		

Tooling - Stamped & Formed Contacts		
Part	Part Number	Description
	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)
	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)
	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)
*	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)
	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021