

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. DIAMETER DIAMETER FIBER TENSILE LOAD TENSILE LOAD BEND RADIUS BEND RADIUS COMPRESSIVE PANDUIT DESCRIPTION ATTENUATION (INSTALLATION) (LONG TERM) STRENGTH P/N COUNT (LONG TERM) (INSTALLATION) FPSN604 4 FPSN606 6 MULTIMODE 62.5/125 OM1 CENTRAL TUBE SINGLE 2.8mm 3.5dB/km @ 850nm FPSN608 8 ARMOR SINGLE JACKET 1.0dB/km @ 1300nm OUTSIDE PLANT CABLE FPSN612 12 FPSN624 24 3.5mm FPSN504 4 FPSN506 6 MULTIMODE 50/125 OM2 В 2.8mm CENTRAL TUBE SINGLE ARMOR SINGLE JACKET 3.5dB/km @ 850nm FPSN508 8 1.5dB/km @ 1300nm OUTSIDE PLANT CABLE FPSN512 12 FPSN524 24 3.5mm FQSNX04 4 6 FQSNX06 MULTIMODE 50/125 OM3 CENTRAL TUBE SINGLE ARMOR_SINGLE_JACKET 2.8mm 3.0dB/km @ 850nm FQSNX08 8 8.5mm 1000 N 500 N 55mm 1.1.0mm 2000 N 1.0dB/km @ 1300nm OUTSIDE PLANT CABLE FQSNX12 12 24 FQSNX24 3.5mm FQSNZ04 4 FQSNZ06 6 MULTIMODE 50/125 OM4 2.8mm CENTRAL TUBE SINGLE ARMOR SINGLE JACKET 3.0dB/km @ 850nm FQSNZ08 8 1.0dB/km @ 1300nm OUTSIDE PLANT CABLE FQSNZ12 12 FQSNZ24 24 3.5mm FPSN904 4 FPSN906 6 SINGLEMODE 9/125 2.8mm CENTRAL TUBE SINGLE ARMOR SINGLE JACKET 0.4dB/km @ 1310nm FPSN908 8 0.3dB/km @ 1550nm OUTSIDE PLANT CABLE FPSN912 12 FPSN924 24 3.5mm TITLE SINGLE ARMOR SINGLE JACKET (SASJ) CENTRAL TUBE FIBER OPTIC CABLE CUSTOMER DRAWING ITEM REVISION NAME M02432CT/00 DATASET FILE NAME M02432CT_DC/00A PART NO. UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: IN [mm] SEE TABLE .xxx ± .010 [0.3] .X ± [8.0] EO. ± xx. ANGLES ± DRAWING NUMBER: 00 SAT WMA TCB RELEASED TO PRODUCTION M02432CT-DS THIRD ANGLE 02-05-14 M02432CT-DS PROJECTION SCALE DRAWN BY DATE REV CHK APR DATE BY DESCRIPTION ECN SAT 02-05-14 SHT 2 OF 2 WMA NONE

 B