



CORE DIMENSIONS					
UNCOATED CORE			35T0231-300		
	MM	INCHES		MM	INCHES
OD	5.84	(.230)	±	.15	(.006)
ID	3.05	(.120)	±	.13	(.005)
TH	2.54	(.100)	±	.13	(.005)
PARYLENE			35T0231-30P		
OD	5.87	(.231)	±	.15	(.006)
ID	3.02	(.119)	±	.13	(.005)
TH	2.57	(.101)	±	.13	(.005)

INITIAL PERMEABILITY
WEIGHT / K

5000
0.53 LBS



ELECTRICAL SPECIFICATION								
	MIN (μ H)	MIN TOL.	NOM (μ H)	MAX (μ H)	MAX TOL.	FREQ. (kHz)	VOLT. (V)	TURNS
L	1.322	(-20%)	1.652	1.983	(+20%)	100	$\leq .00076$	1
Q	10		-	-		100	$\leq .00076$	1

COATING SPECIFICATIONS				
	TYPE	coating thickness (mils.)	Min. DLB VAC	TEST FORCE (LB)
35T0231-300	UNCOATED	-	-	-
35T0231-30P	PARYLENE	0.5	1000	0.30

NOTES:

Rev	Description	Date	INT
A	Original Draft	4/18/1995	JBE
B	TRANSFER TO LOTUS NOTES	11/19/1997	IS
C	REMOVE Q SPECS REACTIVATE PRINT CHANGE PART NUMBER	10/6/1995	JRK
D	REVISED TEMPLATE	4/25/2006	WMM

Date: 4/25/06	DWG #	35T0231-30P-D	Rev:
Drawn By: WMM	Title #	35T0231-30P	D

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.

UNCONTROLLED DOCUMENT