S23F1C-P27MFG0-750S

series_f, type_s2



General information

| Part number | S23F1C-P27MFG0-750S | |
|-------------------|---------------------|-------------|
| Termination | solder | |
| Size | 3 | |
| Locking principle | push | C- C- MILES |
| Coding | 1_halfshell | |
| Cable Diameter | cable_mini_75 | |
| Cable outlet | bend_relief | |
| | | |



Contact insert description

| Number of contacts | 27 |
|----------------------|--------|
| Contact type | pins |
| Contact diameter | 07mm |
| Insulator material | peek |
| Wire cross section | 22_awg |
| Termination | solder |
| Termination diameter | 085mm |
| | |

reverse_gender_on_request

Technical information

| Max. creepage and air clearance distance | 05_mm | 07_mm |
|------------------------------------------|----------|---------------|
| Nominal current single contact | 075_a | iec_60512_5_2 |
| Test voltage | 09_kv_ac | sae_13441 |

safety_text

Mechanical and environmental data

| Degree of protection* | ip50 |
|-----------------------|----------|
| Operating temperature | 40_120_c |
| Mating cycles | 5000 |
| mated_unmated | |

Material and surface treatments

Housing

Contact

m_chrome

cu_alloy_gold

safety_text_2 ul_text illustrative_text