

Filler plugs - HC-K-BS-M40-BK - 1410767

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Filler plug, plastic, size: M40

Filler plugs



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	12.0 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

Ambient conditions

Degree of protection	IP65
	IP65
	IP66 (Tightening torque 3.5 Nm)
Ambient temperature (operation)	-30 °C ... 100 °C

General

Type of the screw connection	M40
Material	Polyamide fiberglass reinforced
Seal material	CR
Thread type on connection side	M40
Torque	3 Nm
Flammability rating according to UL 94	HB
Color	black
	black

Filler plugs - HC-K-BS-M40-BK - 1410767

Technical data

Standards and Regulations

Flammability rating according to UL 94	HB
--	----

Classifications

eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	23111190

ETIM

ETIM 4.0	EC000032
ETIM 5.0	EC000723

UNSPSC

UNSPSC 6.01	30211808
UNSPSC 7.0901	39121408
UNSPSC 11	39121408
UNSPSC 12.01	39121408
UNSPSC 13.2	39121408

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Filler plugs - HC-K-BS-M40-BK - 1410767


Approvals

Approval details

EAC

Drawings

Dimensional drawing



Dimensional drawing