

## Type 3 surge protection device - PRT-S/A-120/FM - 2830605


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Equipment protection plug PRT-S with temperature monitoring, visual and acoustic fault warning and remote indicator contact. Nominal voltage: 120 V



### Key commercial data

Packing unit	1 PCE
GTIN	 4 017918 126698
Weight per Piece (excluding packing)	26.2 GRM
Custom tariff number	85363010
Country of origin	Germany

### Technical data

#### Dimensions

Height	33 mm
Width	31.5 mm
Depth	33 mm

#### Ambient conditions

Degree of protection	IP40
Ambient temperature (operation)	-25 °C ... 75 °C

#### General

Housing material	PA
Inflammability class according to UL 94	V0
Color	black
Standards for air and creepage distances	VDE 0110-1
	IEC 60664-1

# Type 3 surge protection device - PRT-S/A-120/FM - 2830605

## Technical data

### General

Design	Fitted box module
Mounting type	UP/channel installation
Number of positions	2
Direction of action	1L-N & N-PE

### Protective circuit

IEC test classification	III
	T3
EN type	T3
Nominal voltage $U_N$	120 V AC
Arrester rated voltage $U_C$ (L-N)	150 V AC
Arrester rated voltage $U_C$ (L-PE)	150 V AC
Nominal frequency $f_N$	50 Hz
	60 Hz
Nominal current $I_N$	16 A ( $\leq 45^\circ\text{C}$ )
	15 A (UL)
	10 A (CSA)
Operating effective current $I_C$ at $U_C$	$\leq 1.3$ mA
Residual current $I_{PE}$	$\leq 1$ $\mu\text{A}$
Nominal discharge current $I_n$ (8/20) $\mu\text{s}$	1.5 kA
Nominal discharge current $I_n$ (8/20) $\mu\text{s}$ (L-N)	1.5 kA
Nominal discharge current $I_n$ (8/20) $\mu\text{s}$ (L-PE)	1.5 kA
Max. discharge current $I_{max}$ (8/20) $\mu\text{s}$ maximum (L-N)	4.5 kA
Max. discharge current $I_{max}$ (8/20) $\mu\text{s}$ maximum (L-PE)	4.5 kA
Combined surge $U_{OC}$	4 kV
Energy absorption symmetrical	40 J
Energy absorption, asymmetrical	20 J
Voltage protection level $U_p$ (L-N)	$\leq 600$ V
Voltage protection level $U_p$ (L-PE)	$\leq 800$ V
Voltage protection level $U_p$ (N-PE)	$\leq 800$ V
Residual voltage at $I_n$ , (L-N)	$\leq 610$ V
Residual voltage at $I_n$ , (L-PE)	$\leq 330$ V
Response time $t_A$ (L-N)	$\leq 25$ ns
Response time $t_A$ (L-PE)	$\leq 100$ ns
Response time $t_A$ (N-PE)	$\leq 100$ ns
Max. required back-up fuse	16 A (gL/C)
Surge protection fault message	Acoustic, optic, remote indicator contact

## Type 3 surge protection device - PRT-S/A-120/FM - 2830605

### Technical data

#### Remote indicator contact

Connection name	Remote fault indicator contact
Switching function	N/C contact
Connection method	PRT plug-in system
Conductor cross section stranded min.	0.14 mm <sup>2</sup>
Conductor cross section stranded max.	1.5 mm <sup>2</sup>
Conductor cross section solid min.	0.14 mm <sup>2</sup>
Conductor cross section solid max.	1.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	16
Maximum operating voltage U <sub>max</sub> AC	250 V AC
Max. operating current I <sub>max</sub>	3 A (60°C)

#### Standards and Regulations

Standards/specifications	IEC 61643-1 2005
	EN 61643-11/A11 2007

### Classifications

#### eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130806
eCl@ss 7.0	27130806
eCl@ss 8.0	27130806

#### ETIM

ETIM 2.0	EC000942
ETIM 3.0	EC000942
ETIM 4.0	EC000942
ETIM 5.0	EC000942

#### UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610

## Type 3 surge protection device - PRT-S/A-120/FM - 2830605

### Classifications

#### UNSPSC

UNSPSC 13.2	39121620
-------------	----------

### Accessories

#### Accessories

##### Central plate

Central plate - ZP-J/TAE/ST550 WH - 2830362



Central plate, 3x TAE: Range of switches, Jung ST 550, white.

##### Cover frame

Cover frame - AR-J/ST550 WH - 2830359



Cover frame, single: Range of switches, Jung ST 550, white.

### Required add-on products

Flush-type base - PRT-CD-AD1 - 2749673



Flush-type socket base for equipment protection plug PRT-S...

### Additional products

Surge protection device - BXT-M/RS485-TTL - 2749987



Surface-mounted housing with surge protection, for RS-485 interface with with TTL level, mains connection with slot for protective plug PRT-S... (without protective plug)

# Type 3 surge protection device - PRT-S/A-120/FM - 2830605

## Accessories

---

Surge protection device - BXT-M/PLI-24 - 2830113




Surface-mounted housing with surge protection, for RS-485 interface with 24 V signal voltage, mains connection with slot for protective plug PRT-S... (without protective plug)

---

## Drawings

Circuit diagram



1 = signaling  
2 = optional

Dimensioned drawing

