

✓ 54/7454 011598  
 ✓ 54H/74H54 011600  
 ✓ 54LS/74LS54 011599

4-WIDE, 2-INPUT AND-OR-INVERT GATE


ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		V <sub>cc</sub> = +5.0 V ±5%, T <sub>A</sub> = 0°C to +70°C	V <sub>cc</sub> = +5.0 V ±10%, T <sub>A</sub> = -55°C to +125°C	
Plastic DIP (P)	A	7454PC		9A
	B	74H54PC		
	C	74LS54PC		
Ceramic DIP (D)	A	7454DC	5454DM	6A
	B	74H54DC	54H54DM	
	C	74LS54DC	54LS54DM	
Flatpak (F)	C	74LS54FC	54LS54FM	3I
	D	74H54FC	54H54FM	
	E	7454FC	5454FM	


INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74H (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	1.25/1.25	0.5/0.25
Outputs	20/10	12.5/12.5	10/5.0 (2.5)


CONNECTION DIAGRAMS  
PINOUT A




PINOUT B




PINOUT C



PINOUT D



PINOUT E



## DC AND AC CHARACTERISTICS: See Section 3\*

SYMBOL	PARAMETER	54/74	54/74H	54/74LS	UNITS	CONDITIONS	
		Min Max	Min max	Min Max			
ICCH ICCL	Power Supply Current	8.0 9.5	11 14	1.6 2.0	mA	V <sub>IN</sub> = Gnd	V <sub>CC</sub> = Max
						V <sub>IN</sub> = Open	
tPLH tPHL	Propagation Delay	22 15	11 11	15 15	ns	Figs. 3-1, 3-4	

\*DC limits apply over operating temperature range; AC limits apply at T<sub>A</sub> = +25°C and V<sub>CC</sub> = +5.0 V.