

VERA-P1 series



802.11p V2X host-based modules

Flexible and high-performance V2X modules

- Automotive grade 802.11p V2X transceiver modules for infrastructure and vehicles
- Compliance with WAVE and ETSI ITS G5 for US and Europe operation
- Product variants: Non-concurrent dual-channel with antenna diversity or concurrent dual-channel without antenna diversity
- Communication range of more than 1 km (with line-of-sight)
- Operational in ambient temperature -40 °C to +95 °C



24.8 × 29.6 × 3.5 mm



Product description

The VERA-P1 series are compact, embedded transceiver modules that enable development of electronics for Vehicle-to-Everything (V2X) communication systems. These automotive grade modules are designed for applications such as traffic safety and intelligent traffic management. The modules can be used for both in-vehicle units (OBU – On Board Unit) and infrastructure (RSU – Road Side Unit). They provide superior performance compared to V2X systems based on consumer-grade Wi-Fi chipsets, especially at high vehicle speeds and in non-line-of-sight (NLOS) conditions.

The VERA-P1 series includes an integrated MAC/LLC/Baseband processor and the required RF front-end components. The module is connected to a host processor through a USB interface.

Key features

- The pin-to-pin compatible product variants offer operation modes with single channel or concurrent dual-channel
- The transmit mask meets IEEE 802.11p Class C (5.9 GHz band) requirements
- Security acceleration is integrated in the module

	VERA-P173	VERA-P174
Grade		
Automotive	•	•
Professional		
Standard		
Radio		
Wi-Fi IEEE 802.11 standards	p	p
Channel width [MHz]	10	10
Antenna type	2a	2a
OS support		
Linux	•	•
Interfaces		
USB 2.0	1	1
GPIO	8	8
PPS	1	1
Features		
Antenna diversity	•	#
Single channel operation	•	•
Concurrent dual-channel operation		#

2a = 2 pins for 2 external antennas

= User can configure as dual-channel or diversity



Features

Standards conformance	IEEE 802.11p (IEEE 802.11-2016) ETSI ES 302 663 IEEE 1609.4 - 2016
Frequency band	5.9 GHz
Antenna	2 antenna pins for external 5 GHz antennas
Output power	0 to +23 dBm
Receiver sensitivity	-98 dBm @ 3 Mbit/s
Data rates	3 to 27 Mbit/s

Software features

Operating modes	Non-concurrent dual-channel with antenna diversity Concurrent dual-channel without antenna diversity
Radio channel measurements	Channel utilization Channel active ratio Per-channel statistics Received signal and noise power levels

Interfaces

Host interface	USB 2.0
Other interfaces	GPIO and 1PPS

Package

Dimensions	24.8 x 29.6 x 3.5 mm
Pin-out	160 pins LCC (Leadless Chip Carrier)

Environmental data, quality & reliability

Operating temperature	-40 °C to +95 °C
According to Baseband/radio AEC-Q100 and ISO 16750-4	

Electrical data

Power supply	3.3 V and 5 V
Power consumption	4 W (max)

Certifications and approvals

Europe (ETSI RED)	
US (FCC parts 90, 95L)	

Support products

The VERA-P1 evaluation kit includes an evaluation board with full access to the module interfaces. The board has SMA connectors for connecting external antennas and two antennas.

EVK-VERA-P174	Evaluation kit for VERA-P1 modules
---------------	------------------------------------

Product variants

VERA-P173	Module with single channel and diversity
VERA-P174	Module with single channel and diversity, or dual-channel

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the [product data sheet](#).

Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.
Copyright © 2020, u-blox AG