



ISO9001:2008 Certified

Mechanical Specifications (mm)

	D:	22.0	± max
	T:	5.0	± max
	Lead Diameter	1.0	± nom
	S:	7.8	± nom
	L:	38.0	± nom
	Coating Lead Run Down (straight Leads)	5.0	± max
	B:	9.22	± nom
	C:	3.65	± nom



Electrical Specifications

	Resistance:	2.5	Ω	± 20 %
Max Steady State Current upto 65°C:	8.00	A		
Max Rec. Energy Rating:	90	J		
Actual Failure Instantaneous Energy:	200	J		
Maximum Capacitance @ 120 VAC:	6,251	µf		
Maximum Capacitance @ 240 VAC:	1,562	µf		
Resistance @ 100% Max Current:	0.06	Ω		
Resistance @ 50% Max Current:	0.14	Ω		
Body Temperature at 100% Max Current:	162.00	°c		
Dissipation Constant:	32.4	mw/°c		
Thermal Time Constant:	94	Sec.		
Material Type (for Beta and Curve):				

SL22 2R508	
Date: 11/11/2008	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: a