



REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	D1	ECR-20-006499	06MAY2020	RK	HL

## PD-Caps Semirigid Polyolefin Heat-shrinkable End Caps

As Supplied



After Unrestricted Recovery



Outer Jacket  
Heat shrinkable sem-irigid, irradiated,  
modified polyolefin

Inner Wall  
Adhesive

**Table 1: Dimensions mm (inches)**

Size	A	B Minimum	C Minimum	D Maximum	W Nominal
1/8	25.40 (1.000) ± 3.00 (0.125)	13.97 (0.550)	3.18 (0.125)	0.58 (0.023)	1.22 (0.048)
3/16	30.15 (1.187) ± 3.81 (0.150)	16.51 (0.650)	4.75 (0.187)	1.52 (0.060)	1.57 (0.062)
1/4	25.00 (0.984) ± 3.00 (0.125)	16.51 (0.650)	6.35 (0.250)	2.03 (0.080)	1.98 (0.078)
1/4	28.58 (1.125) ± 3.00 (0.125)	16.51 (0.650)	6.35 (0.250)	2.03 (0.080)	1.98 (0.078)
1/4	35.00 (1.378) ± 3.81 (0.150)	16.51 (0.650)	6.35 (0.250)	2.03 (0.080)	1.98 (0.078)
3/8	31.12 (1.225) ± 3.81 (0.150)	19.69 (0.775)	9.53 (0.375)	2.28 (0.090)	2.08 (0.082)
1/2	32.26 (1.270) ± 3.30 (0.130)	21.59 (0.850)	12.70 (0.500)	2.28 (0.090)	2.54 (0.100)
1/2	50.00 (1.968) ± 3.81 (0.150)	21.59 (0.850)	12.70 (0.500)	2.28 (0.090)	2.54 (0.100)

**Color:** Black

**Specification:** Formed from semirigid, encapsulant-lined polyolefin tubing per TEC-108-120027

© 2019 TE Connectivity. All Rights Reserved.



DIMENSIONS: INCHES	DWN	10AUG2017	MATERIAL	-	FINISH	-
	CHK	J. Bitter	TE Connectivity			
TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD	T. Licko				
	PRODUCT SPEC	T. Licko	NAME	PD-Caps Semirigid Polyolefin Heat-Shrinkable End Caps		
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -	APPLICATION SPEC	108-120027	SIZE	A4	CAGE CODE	06090
	WEIGHT	-	DRAWING NO	C-PD-CAPS		RESTRICTED TO
CUSTOMER DRAWING			SCALE	None	SHEET	1 OF 1
					REV	D1