P	ROPRIETARY INFORMATION:	REVISION					
	ROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR	REV	DESCRIPTION	DATE	APPROVE		
	USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK,INC.		INITIAL RELEASE	06/30/00	PS		
11	tombiteb excel the steen leb it withit bit debitek, ite.	В	UPDATE TO NEW FORMAT, RFS.10695, BS	04/17/07	BS		
		C	UPDATE END 'B', RFS.18277, BS	03/12/10	BS		
	2520±50						
A BROWN GRN/YEL BLUE			GRN/YEL GRN/YEL Strip 6±1 BROWN BLUE Strip 6±1 76±5	A STATE OF	Л HS		

GENERAL SPECIFICATIONS:

CABLE TYPE / SIZE:
TEMPERATURE RATING:
CONDUCTOR COLORS:
CABLE JACKET COLOR:
OVERALL LENGTH (L):
CABLE OUTER DIAMETER:
END 'A' PLUG:
END 'B' :
APPROVALS PLUG:
APPROVALS CABLE:

RATING:

10A / 250V AC H05VV-F, $3 \times 1.0 \text{ mm}^2$ 70° C BROWN / BLUE/ GREEN-YELLOW BLACK 2520 \pm 50 mm 7.0 \pm 0.1 mm CEE 7/7 SEE TERMINATION TABLE VDE, N, S, D, FI, KEMA, CEBEC, OVE VDE, N, S, D, FI, KEMA, CEBEC, OVE

CONDUCTOR TERMINATION TABLE:

PACKING:

BULK PACKED, BUNDLES OF 25. MAXIMUM SHIPPING CARTON WEIGHT IS 30 KG.

NOTES:

1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).

	Wire	Color	ROJ ± 5	5 mm	RIJ±1 mm	Te	rminal						
	Ground	Green-Yellow	102	2	6	Strip							
]	Neutral	Blue	76	5	6	Strip							
	Line	Brown	76	5	6		Strip						
						DASH NO.	PART NO	REV.			DESCRIPTION		NOTES
						TABULATION BLOCK							
							DECI	MALS /- 0.1 /005	NCES: ANGULAR +/- 1°		186 Veterans Dr. Nortl Tel. 201-784-1000 Fa		
		Foot Note: Globtek Inc. will not be liable for the safety and performance of these power	for the	Limitation of Use: Globtek product are not authorized for use as mission critical components in life support,	INIT.BY: BS	T.BY: BS DATE: .xx		cx +/013		DWG TITLE: EUROPEAN NON-DET	ACHABLE CORDSET	[
	product if unauthorized access and repair occurs. End user should consult the appl ble UL _c CSA or EN Standards for prope	and repair h t the applica- a	hazardous environment, nuclear or aircraft applications without prior written		DRAWN: NF	DATE: 04/17/07	FSCN G, CC		SIZE A			C REV.	
r		installation instruction.	ior proper a	proper approvar from the CEO of Olo		APRVD: HM	DATE: 04/17/07	SCAI	CALE: NONE		PART NO: 23144272M5002(R)		SHEET 1/1