

Converter - Brake - Inverter Module



XPT IGBT

Three Phase Rectifier	Brake Chopper	Three Phase Inverter
$V_{RRM} = 1600 \text{ V}$	$V_{CES} = 1200 \text{ V}$	$V_{CES} = 1200 \text{ V}$
$I_{DAVM} = 105 \text{ A}$	$I_{C25} = 17 \text{ A}$	$I_{C25} = 17 \text{ A}$
$I_{FSM} = 320 \text{ A}$	$V_{CE(sat)} = 1.8 \text{ V}$	$V_{CE(sat)} = 1.8 \text{ V}$

Preliminary data

Part name (Marking on product)

MIXA10WB1200TED



E 72873

Pin configuration see outlines.

Features:

- Easy paralleling due to the positive temperature coefficient of the on-state voltage
- Rugged XPT design
(Xtreme light Punch Through) results in:
 - short circuit rated for 10 μsec .
 - very low gate charge
 - low EMI
- Thin wafer technology combined with the XPT design results in a competitive low $V_{CE(sat)}$
- SONIC™ diode
 - fast and soft reverse recovery
 - low operating forward voltage

Application:

- AC motor drives
- Solar inverter
- Medical equipment
- Uninterruptible power supply
- Air-conditioning systems
- Welding equipment
- Switched-mode and resonant-mode power supplies

Package:

- "E2-Pack" standard outline
- Insulated copper base plate
- Soldering pins for PCB mounting
- Temperature sense included

Output Inverter T1 - T6

Ratings

Symbol	Definitions	Conditions	min.	typ.	max.	Unit
V_{CES}	collector emitter voltage	$T_{VJ} = 25^\circ C$		1200		V
V_{GES}	max. DC gate voltage	continuous		± 20		V
V_{GEM}	max. transient collector gate voltage	transient		± 30		V
I_{C25}	collector current	$T_C = 25^\circ C$		17		A
I_{C80}		$T_C = 80^\circ C$		12		A
P_{tot}	total power dissipation	$T_C = 25^\circ C$		60		W
$V_{CE(sat)}$	collector emitter saturation voltage	$I_C = 9 A; V_{GE} = 15 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$	1.8 2.1	2.1	V
$V_{GE(th)}$	gate emitter threshold voltage	$I_C = 0.3 mA; V_{GE} = V_{CE}$	$T_{VJ} = 25^\circ C$	5.5	6.0	V
I_{CES}	collector emitter leakage current	$V_{CE} = V_{CES}; V_{GE} = 0 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$	0.01 0.1	0.7	mA mA
I_{GES}	gate emitter leakage current	$V_{GE} = \pm 20 V$			500	nA
$Q_{G(on)}$	total gate charge	$V_{CE} = 600 V; V_{GE} = 15 V; I_C = 10 A$		27		nC
$t_{d(on)}$ t_r $t_{d(off)}$ t_f E_{on} E_{off}	turn-on delay time current rise time turn-off delay time current fall time turn-on energy per pulse turn-off energy per pulse	inductive load $V_{CE} = 600 V; I_C = 10 A$ $V_{GE} = \pm 15 V; R_G = 100 \Omega$	$T_{VJ} = 125^\circ C$	70 40 250 100 1.1 1.1		ns ns ns ns mJ mJ
RBSOA	reverse bias safe operating area	$V_{GE} = \pm 15 V; R_G = 100 \Omega;$	$T_{VJ} = 125^\circ C$ $V_{CEK} = 1200 V$		30	A
SCSOA	short circuit safe operating area					
t_{sc} I_{sc}	short circuit duration short circuit current	$V_{CE} = 900 V; V_{GE} = \pm 15 V;$ $R_G = 100 \Omega$; non-repetitive	$T_{VJ} = 125^\circ C$	40	10	μs A
R_{thJC}	thermal resistance junction to case	(per IGBT)			2.0	K/W

Output Inverter D1 - D6

Ratings

Symbol	Definitions	Conditions	min.	typ.	max.	Unit
V_{RRM}	max. repetitive reverse voltage	$T_{VJ} = 25^\circ C$		1200		V
I_{F25}	forward current	$T_C = 25^\circ C$		19		A
I_{F80}		$T_C = 80^\circ C$		13		A
V_F	forward voltage	$I_F = 10 A; V_{GE} = 0 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$	1.95 1.85	2.2	V V
Q_{rr} I_{RM} t_{rr} E_{rec}	reverse recovery charge max. reverse recovery current reverse recovery time reverse recovery energy	$V_R = 600 V$ $di_F/dt = - A/\mu s$ $I_F = 10 A; V_{GE} = 0 V$	$T_{VJ} = 125^\circ C$	tbd tbd tbd tbd		μC A ns mJ
R_{thJC}	thermal resistance junction to case	(per diode)			2.4	K/W

 $T_C = 25^\circ C$ unless otherwise stated

Brake T7

Ratings

Symbol	Definitions	Conditions	min.	typ.	max.	Unit
V_{CES}	collector emitter voltage	$T_{VJ} = 25^\circ C$		1200		V
V_{GES}	max. DC gate voltage	continuous		± 20		V
V_{GEM}	max. transient collector gate voltage	transient		± 30		V
I_{C25}	collector current	$T_c = 25^\circ C$	17		A	
I_{C80}		$T_c = 80^\circ C$	12		A	
P_{tot}	total power dissipation	$T_c = 25^\circ C$	60		W	
$V_{CE(sat)}$	collector emitter saturation voltage	$I_c = 9 A; V_{GE} = 15 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$	1.8 2.1	2.1	V
$V_{GE(th)}$	gate emitter threshold voltage	$I_c = 0.3 mA; V_{GE} = V_{CE}$	$T_{VJ} = 25^\circ C$	5.5	6.0	V
I_{CES}	collector emitter leakage current	$V_{CE} = V_{CES}; V_{GE} = 0 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$		0.1	mA
I_{GES}	gate emitter leakage current	$V_{GE} = \pm 20 V$			500	nA
$Q_{G(on)}$	total gate charge	$V_{CE} = 600 V; V_{GE} = 15 V; I_c = 10 A$	27			nC
$t_{d(on)}$	turn-on delay time	$\left. \begin{array}{l} t_r \\ t_{d(off)} \\ t_f \\ E_{on} \\ E_{off} \end{array} \right\}$ inductive load $V_{CE} = 600 V; I_c = 10 A$ $V_{GE} = \pm 15 V; R_G = 100 \Omega$	70			ns
t_r	current rise time		40			ns
$t_{d(off)}$	turn-off delay time		250			ns
t_f	current fall time		100			ns
E_{on}	turn-on energy per pulse		1.1			mJ
E_{off}	turn-off energy per pulse		1.1			mJ
RBSOA	reverse bias safe operating area	$V_{GE} = \pm 15 V; R_G = 100 \Omega;$ $V_{CEK} = 1200 V$		30		A
SCSOA	short circuit safe operating area	$V_{CE} = 900 V; V_{GE} = \pm 15 V;$ $R_G = 100 \Omega$; non-repetitive	$T_{VJ} = 125^\circ C$	10	μs	A
I_{sc}	short circuit duration					
I_{sc}	short circuit current			40		
R_{thJC}	thermal resistance junction to case	(per IGBT)			2.0	K/W

Brake Chopper D7

Ratings

Symbol	Definitions	Conditions	min.	typ.	max.	Unit
V_{RRM}	max. repetitive reverse voltage	$T_{VJ} = 25^\circ C$		1200		V
I_{F25}	forward current	$T_c = 25^\circ C$	12		A	
I_{F80}		$T_c = 80^\circ C$	8		A	
V_F	forward voltage	$I_F = 5 A; V_{GE} = 0 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$	1.95 1.85	2.2	V
I_R	reverse current	$V_R = V_{RRM}$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$	0.5	0.5	mA
Q_{rr}	reverse recovery charge	$\left. \begin{array}{l} I_{RM} \\ t_{rr} \\ E_{rec} \end{array} \right\}$ $V_R = 600 V$ $di_F/dt = tbd A/\mu s$ $I_F = 10 A; V_{GE} = 0 V$	$T_{VJ} = 125^\circ C$	tbd	μC	A
I_{RM}	max. reverse recovery current					
t_{rr}	reverse recovery time					
E_{rec}	reverse recovery energy					
R_{thJC}	thermal resistance junction to case	(per diode)			3.4	K/W

 $T_c = 25^\circ C$ unless otherwise stated

Input Rectifier Bridge D11 - D16


Ratings						
Symbol	Definitions	Conditions	min.	typ.	max.	Unit
V_{RRM}	max. repetitive reverse voltage		$T_{VJ} = 25^\circ\text{C}$		1600	V
I_{FAV}	average forward current	sine 180°	$T_C = 80^\circ\text{C}$		37	A
I_{DAVM}	max. average DC output current	rect.; $d = 1/3$	$T_C = 80^\circ\text{C}$		105	A
I_{FSM}	max. forward surge current	$t = 10 \text{ ms}; \text{sine } 50 \text{ Hz}$	$T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$		320 280	A A
I^2t	I^2t value for fusing	$t = 10 \text{ ms}; \text{sine } 50 \text{ Hz}$	$T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$		510 390	A ² s A ² s
P_{tot}	total power dissipation		$T_C = 25^\circ\text{C}$		110	W
V_F	forward voltage	$I_F = 50 \text{ A}$	$T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$	1.34 1.34	1.7	V V
I_R	reverse current	$V_R = V_{RRM}$	$T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$		0.02	mA mA
R_{thJC}	thermal resistance junction to case	(per diode)			1.1	K/W

Temperature Sensor NTC

Ratings						
Symbol	Definitions	Conditions	min.	typ.	max.	Unit
R_{25}	resistance		$T_C = 25^\circ\text{C}$	4.75	5.0	kΩ
$B_{25/50}$					3375	K

Module

Ratings						
Symbol	Definitions	Conditions	min.	typ.	max.	Unit
T_{VJ}	operating temperature		-40		125	°C
T_{VJM}	max. virtual junction temperature				150	°C
T_{stg}	storage temperature		-40		125	°C
V_{ISOL}	isolation voltage	$I_{ISOL} \leq 1 \text{ mA}; 50/60 \text{ Hz}$			2500	V~
CTI	comparative tracking index				-	
M_d	mounting torque (M5)		3		6	Nm
d_s	creep distance on surface		6			mm
d_A	strike distance through air		6			mm
$R_{pin-chip}$	resistance pin to chip				5	mΩ
R_{thCH}	thermal resistance case to heatsink	with heatsink compound		0.02		K/W
Weight					180	g

Equivalent Circuits for Simulation


Ratings						
Symbol	Definitions	Conditions	min.	typ.	max.	Unit
V_0	rectifier diode	D8 - D13	$T_{VJ} = 150^\circ\text{C}$		0.88	V
R_0					9	mΩ
V_0	IGBT	T1 - T6	$T_{VJ} = 150^\circ\text{C}$		1.1	V
R_0					153	mΩ
V_0	free wheeling diode	D1 - D6	$T_{VJ} = 150^\circ\text{C}$		1.1	V
R_0					90	mΩ
V_0	IGBT	T7	$T_{VJ} = 150^\circ\text{C}$		1.1	V
R_0					153	mΩ
V_0	free wheeling diode	D7	$T_{VJ} = 150^\circ\text{C}$		1.15	V
R_0					170	mΩ

$T_C = 25^\circ\text{C}$ unless otherwise stated

IXYS reserves the right to change limits, test conditions and dimensions.


20090804b

Circuit Diagram




Outline Drawing

Dimensions in mm (1 mm = 0.0394")



Product Marking



2D Data Matrix:
FOSS-ID 6 digits
Batch # 6 digits

Part number

M = Module
I = IGBT
A = MPT
X = Parallel Legs
10 = Current Rating [A]
WB = 6-Pack + 3~ Rectifier Bridge & Brake Unit
1200 = Reverse Voltage [V]
T = NTC
ED = E2-Pack

Ordering	Part Name	Marking on Product	Delivering Mode	Base Qty	Ordering Code
Standard	MIXA10WB1200 TED	MIXA10WB1200TED	Box	6	508061

IXYS reserves the right to change limits, test conditions and dimensions.

20090804b




Fig. 1 Typ. output characteristics




Fig. 2 Typ. output characteristics




Fig. 3 Typ. tranfer characteristics




Fig. 4 Typ. turn-on gate charge




Fig. 5 Typ. switching energy vs. collector current




Fig. 6 Typ. switching energy vs. gate resistance

IXYS reserves the right to change limits, test conditions and dimensions.




Fig. 7 Typ. forward characteristics




Fig. 8 Typical reverse recovery charge
 Q_{rr} versus. di_F/dt (125°C)




Fig. 9 Typical peak reverse current
 I_{rr} versus di_F/dt (125°C)




Fig. 10 Typ. recovery time t_{rr} vs. di/dt (125°C)




Fig. 11 Typ. recovery energy E_{rec} vs. di_F/dt (125°C)




Fig. 8 Transient thermal impedance

20090804b

IXYS reserves the right to change limits, test conditions and dimensions.