



### Main

Device Application	Standard mill switch Universal mill switch Heavy duty
Range of Product	T
Series name	Severe duty

### Complementary

[Ith] conventional free air thermal current	20 A
[Ui] rated insulation voltage	600 V
Base plate style	Style D
Body Material	Cast zinc
Contact code designation	P600 A600
Contacts material	Silver flashed copper
Contact operation	Snap action
Positive opening	Without
Switch actuation	CCW
Torque Value	12 lbf.in (1.36 N.m)

### Environment

Electrical shock protection class	Class 0
IP Degree of Protection	IP67 IP66 IP65
NEMA Degree of Protection	NEMA 1/2/4/12/13
Product Certifications	CSA UL UL Listed CE
Protective treatment	Corrosion resistant gray paint
Shock resistance	30 gn
Standards	UL 508

### Ordering and shipping details

Category	21497-9007 FT,T OILTIGHT AND FOUNDRY
Discount Schedule	DS1
GTIN	785901752301
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.90 in (7.366 cm)
Package 1 Width	2.50 in (6.35 cm)
Package 1 Length	5.30 in (13.462 cm)
Package 1 Weight	2.50 lb(US) (1.134 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------