### K41F1C-P06LFG0-150S

# series\_f, type\_k4



#### **General information**

| Part number       | K41F1C-P06LFG0-150S |
|-------------------|---------------------|
| Termination       | solder              |
| Size              | 1                   |
| Locking principle | break, push         |
| Coding            | 1_halfshell         |
| Cable Diameter    | cable_mini_15       |
| Cable outlet      | bend_relief         |







# **Contact insert description**

| Number of contacts   | 6       |
|----------------------|---------|
| Contact type         | sockets |
| Contact diameter     | 07mm    |
| Insulator material   | peek    |
| Wire cross section   | 22_awg  |
| Termination          | solder  |
| Termination diameter | 085mm   |

 $reverse\_gender\_on\_request$ 

## **Technical information**

| Max. creepage and air clearance distance | 06 <sub>mm</sub> | 08 <sub>mm</sub> |
|--|------------------|------------------|
| Nominal current single contact           | 075_a            | iec_60512_5_2    |
| Nominal current insert                   | 5,625 A          | vde_0298_4       |
| Test voltage                             | 1_kv_ac          | sae_13441        |

safety\_text

### Mechanical and environmental data

| Degree of protection* | ip68     |
|-----------------------|----------|
| Operating temperature | 40_120_c |
| Mating cycles         | 5000     |

mated

# Material and surface treatments

| Housing       | m_chrome      |  |
|---------------|---------------|--|
| Contact       | cu_alloy_gold |  |
| cofety text 2 |               |  |

safety\_text\_2 ul\_text illustrative\_text