




Item	Specification
No. of conductors	導體芯 N 6P
Pitch	間距 P 0.5±0.05
Total Pitch	總間距 PT 2.5±0.05
Total Length	總長度 L 76±1
Insulation Length	絕緣長度 IL 69±1
Margin Width	邊緣寬度 M 0.5±0.05
Total Width	總寬度 W 3.5±0.05
Strip Length	線口長度 S1 3.5±0.5
Strip Length	線口長度 S2 3.5±0.5
Reinforeing tape length	補強板長度 B1 6±1
Reinforeing tape length	補強板長度 B2 6±1
Slanting	線口傾斜度 A ≤0.3
Over lap	衝孔 /
Terminal thickness	插入厚度 T1/T2 0.32/0.32±0.03
Thickness insulation	線身厚度 T 0.155±0.02
Conductor thickness	導體厚度 Ct 0.035±0.005
Conductor width	導體寬度 Cw 0.3±0.03
Supporting Tape Color	補強板顏色 Blue
PET(Supporting Tape)	補強板規格 0.225
PET(Insulation)	絕緣膠規格 0.06 (Printing HF105°)
PET(Insulation)	絕緣膠規格 0.06 (White HF105°)
Storage Temperature Range	存儲溫度/濕度 10°C~35°C/30~65RH%



RoHS Compliant

				DRAWN:
				CHECKED:
				APPROVAL:
A	07-May-2022			
REV	DATE	FILE	BY	

GENERAL TOLERANCE: .X=±0.30 .XX=±0.20 .XXX=±0.15
UNIT: MM
SCALE: 1:1
SHEET: 1 / 1
PROJECTION:

<b>CnC Tech</b> Industrial Cable and Connector Technology	
DESCRIPTION: 0.5MM 6P L=76MM FLAT FLEXIBLE CABLE	SIZE A4
PART NO: 310-06-0076-A	

A  
B  
C  
D