



Technical Data Sheet



CERTIFICATIONS



SPR-VA-PVC



Protective metal conduit for the sensor technology, strip-wound, s profile, PVC sheathing, non flame propagating acc. to DIN EN IEC 61386-23

Material: Conduit: Stainless steel, Sheathing: PVC

Temperature:
-25°C ... +90°C
-13°F ... +194°F

Protection Class: IP 68

Color: Black

Aerosusa.com
service@aerosusa.com
855.393.9905

"Uns surpassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103



Technical Data Sheet

Aerosusa.com
service@aerosusa.com
855.393.9905

Product #	Color	ID (in)	OD (in)	Stat BR (in)	Dyn BR (in)	lb/ft	PU
2010.182.003	Black	0.12	0.24	0.59	1.46	0.0269	164 FT
2010.182.004	Black	0.16	0.28	0.67	1.77	0.0336	164 FT
2010.182.005	Black	0.20	0.31	0.79	1.97	0.0403	164 FT
2010.182.006	Black	0.24	0.35	0.98	2.36	0.0538	164 FT
2010.182.008	Black	0.31	0.43	1.38	3.54	0.0605	164 FT
2010.182.009	Black	0.35	0.47	1.50	3.94	0.0706	164 FT

"Unsurpassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103