



RJI Ethernet stranded cable,
AWG 26/7, 2x4x0.5/1.0, outdoor,
Cat. 6A, PVC, black

- Temperature range: -20°C ... +70°C

20	3345421020003
19	33454210190003
18	33454210180003
17	33454210170003
16	33454210160003
15	33454210150003
14	33454210140003
13	33454210130003
12	33454210120003
11	33454210110003
10	33454210100003
9	33454210090003
8	33454210080003
7	33454210070003
6	33454210060003
5	33454210050003
4	33454210040003
3	33454210030003
2	33454210020003
1	33454210010003

Cont. no.	Part no.	Type of cable	Dim. a[m]
1	33454210010003		1
2	33454210020003		2
3	33454210030003		3
4	33454210040003		4
5	33454210050003		5
6	33454210060003		6
7	33454210070003		7
8	33454210080003		8
9	33454210090003		9
10	33454210100003		10
11	33454210110003		11
12	33454210120003		12
13	33454210130003		13
14	33454210140003		14
15	33454210150003		15
16	33454210160003		16
17	33454210170003		17
18	33454210180003		18
19	33454210190003		19
20	33454210200003		20

		All Dimensions in mm Original Size DIN A3		Scale 2:1		Free size tol.		Ref.	
All rights reserved Department EC PD - RO		Created by MUNTEANV		Inspected by AVRAM		Standardisation HOFFMANN		Date 2015-05-20	
HARTING Electronics GmbH D-32339 Espelkamp		Title HARTING PushPull RJ45 Cable Assembly				Doc-Key / ECM-Nr. 100223972/UGD/007/B 50000089209		State Final Release	
		Type TB		Number 3345421XXX0003		Rev. B		Page 1/1	