2-2170808-6 ACTIVE

zQSFP+/QSFP28

TE Internal #: 2-2170808-6

QSFP, QSFP+ & zQSPF+, Cage Assembly, 1 x 2, Internal/External EMI Springs, Included Lightpipe, Standard, Data Rate (Max) 28 Gb

/s, zQSFP+/QSFP28

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > QSFP, QSFP+ & zQSPF+











Pluggable I/O Product Type: Cage Assembly

Port Matrix Configuration: 1 x 2

EMI Containment Feature Type: Internal/External EMI Springs

Thermal Accessory Type Included: Heat Sink

Included Lightpipe: Yes

Features

Product Type Features

Form Factor	QSFP28/56
Cage Type	Ganged
Pluggable I/O Product Type	Cage Assembly
Thermal Accessory Type Included	Heat Sink
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Configuration Features Port Matrix Configuration	1 x 2
	1 x 2 2
Port Matrix Configuration	
Port Matrix Configuration Number of Ports	2
Port Matrix Configuration Number of Ports Lightpipe Configuration	2 Dual Round



Rody Fost

Body Features	
Heat Sink Finish	Anodized Black
Heat Sink Style	Pin
Heat Sink Height Class	Networking
Heat Sink Height	13.5 mm[.531 in]
Contact Features	
PCB Contact Termination Area Plating Material	Tin
Termination Features	

Termination Post & Tail Length

Termination Post & Tail Length	2.05 mm[.081 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit

Mechanical Attachment

Connector Mounting Type	Board Mount
-------------------------	-------------

Housing Features

Cage Material	Nickel Silver
---------------	---------------

Dimensions

PCB Thickness (Recommended)	1.57 mm[.062 in]
-----------------------------	------------------

Usage Conditions

Operating Temperature Range -40 – 85 °C[-40 – 185 °F]

Operation/Application

For Use With Pluggable I/O Products	QSFP28 Cable Assembly, QSFP28 MSA Compatible Transceiver
Pluggable I/O Applications	SFP+ Stacked Belly-to-Belly
Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Method	Box & Tray	

Other

EMI Containment Feature Type	Internal/External EMI Springs
Included Lightpipe	Yes
Enhancements	Standard



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













TE Part # CAT-C11-N490325 QSFP28-Four SFP+ Cable Assembly: 26 AWG



TE Part # CAT-Q17-N490325 QSFP56 to QSFP56 Cable Assembly: 30 AWG



TE Part # CAT-Q17-N49033 QSFP56-Two QSFP56 Cable Assembly: 30 AWG



QSFP56 to QSFP56 Cable Assembly: 26 AWG



TE Part # CAT-Q17-N49011 QSFP56-Four SFP56 Cable Assembly: 30 AWG



TE Part # CAT-Q17-N490333 QSFP56-Four SFP56 Cable Assembly: 26 AWG



TE Part # 1551920-2 zQSFP+ connector assembly





Also in the Series | zQSFP+/QSFP28



Pluggable I/O Cable Assemblies(81)



Customers Also Bought

















Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-2170808-6_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-2170808-6_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-2170808-6_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English