



Main

Device short name	A
Enclosure type	Standard environment enclosure indoor
Product Specific Application	Mechanically alternating the operation of two pumps or motors
Switch application	Standard

Complementary

Electrical Connection	Screw clamp terminal
Material	Stainless steel float/rod Nitrile (Buna-N) seal ring
Maximum Horse Power Rating	3 Hp 230 V AC, 1 phase 5 Hp 230 V AC, 3 phase 1 Hp 460/575 V AC, 3 phase 3 Hp 115 V AC, 1 phase 2 hp 115 V AC, 3 phase
Mounting Support	Flange
Number of poles	2
Permissible voltage	575 V AC
Switch Function	DPST

Environment

NEMA Degree of Protection	NEMA 1
---------------------------	--------

Ordering and shipping details

Category	21601-9037,9038 COMMERCIAL FLOAT SWITCHES
Discount Schedule	CP7G
GTIN	785901591184
Nbr. of units in pkg.	1
Package weight(Lbs)	4.70 lb(US) (2.132 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	11.76 in (29.871 cm)
Package 1 width	4.63 in (11.76 cm)
Package 1 Length	29.87 in (75.872 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------