





PRODUCT NO.
74896-XXX
SEE NOTE 6
74896-XXXLF



STANDARD LATCH FINGER FOR CABLE TIE BELOW LATCH FINGER AND EASIEST ACCESS TO LATCH FINGER

SHORT LATCH FINGER FOR CABLE TIE ABOVE LATCH FINGER AND LARGER CABLE SIZE CAPACITY



NOTE: THIS DRAWINGS COVERS SPECIAL KITS WITH ONE OF MORE OF THE FOLLOWING:
SPECIAL LATCHES
SPECIAL COVERS
SELECTIVE LOADED CONTACTS
SEE CUSTOMER DRAWING 72477 FOR STANDARD 4X12 METRAL CABLE CONNECTOR KITS.

mat'l. code		surface ASME Y14.5		tolerance ASME Y14.5		projection		product family METRAL		
ltr	ecn no	dr	date	tolerances unless otherwise specified		MM		title		
A	v00247	JRV	1/20/00	angles	lines	scale 1:1		4x12 UNSHIELDED		
B	v03-0072	HTB	1/17/03					2006-06-26		
C	v06-0234	JRV	3/9/06					dwg no		
D	v06-0622	JRV	2006-06-26	dr	J.R. VOLSTORF	1/20/00	sheet 1 of 2		size	
				engr	J.R. VOLSTORF	1/20/00	FCI		74896	
				chr	J.R. VOLSTORF	1/20/00	type		CUSTOMER Drawing	
				appd	J.R. VOLSTROF	1/20/00				
sheet index	revision sheet	D	D							
		1	2							

CONNECTOR KIT	COVER NON-LATCH SIDE	COVER LATCH SIDE	LATCH FINGER		CONNECTOR SUB-ASSEMBLY POSITIONS A&B	CONNECTOR SUB-ASSEMBLY POSITIONS C&D	WIRE GAGE	CONTACT PLATING
			NUMBER	COLOR				
74896-001	NONE	NONE	70289-001	BLACK	72394-9211	72394-9211	24-26	0.8um GXT
74896-002	NONE	NONE	70289-001	BLACK	72394-1211	72394-1211	24-26	0.8um GOLD
74896-001LF	NONE	NONE	70289-001LF	BLACK	72394-9211LF	72394-9211LF	24-26	0.8um GXT
74896-002LF	NONE	NONE	70289-001LF	BLACK	72394-1211LF	72394-1211LF	24-26	0.8um GOLD

NOTES:

- SEE APPLICATION SPECIFICATION GES-20-002 FOR INSTRUCTIONS ON WIRE INSERTION AND ASSEMBLY OF COMPONENTS FOR CONNECTORS.
 - PLUGS INTO STANDARD METRAL 4-ROW HEADERS AND SHROUDS.
 - MAXIMUM CABLE DIAMETER
STANDARD LATCH (70289 TYPE) = 6.0mm
SHORT LATCH (72389 TYPE) = 9.0mm
* THE USE OF MULTIPLE CABLES OR THE STRIPPING OF THE CABLE JACKET WILL ALLOW THE USER TO OVERCOME SOME THE RESTRICTIONS.
 - THE PRODUCTS WHERE THE PART NUMBERS END IN LF MEET THE EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
 - THESE PRODUCTS LISTED ON THIS DRAWING WILL NOT WITHSTAND WAVE SOLDER OR REFLOW OPERATIONS.
- Ⓢ FOR LEADFREE PART NUMBERS, ADD AN 'LF' SUFFIX.
EXAMPLE: 74896-001LF

MATERIAL

INSULATORS, COVERS AND KEYS
GLASS FILLED 612 POLYAMIDE (UL 94 V-0)
LATCH FINGERS
POLYETHERIMIDE (UL 94 V-0)
CONTACTS
PHOSPHOR BRONZE
SOLDER FINISH ON IDC DIMPLES

OPTIONAL CODING KEYS

PART NUMBER 72388-OAA1
18 VARIETIES AA = 0 TO 18
USE IN CONJUNCTIONS WITH HEADER CODING
KEYS 70274-001 KEYS 1 TO 18 RESPECTIVELY

mat'l. code		surface ASME Y14.5		tolerance ASME Y14.5		projection 		product family METRAL		
ltr	ecn no	dr	date	tolerances unless otherwise specified		MM 		title 4x12 UNSHIELDED CABLE CONNECTOR KIT		
d				angles	file	scale 1:1		dwg no 74896		
				dr	J.R. VOLSTORF	1/20/00			sheet 2 of size A4	
				eng	J.R. VOLSTORF	1/20/00				
				chr	J.R. VOLSTORF	1/20/00				
				appd	J.R. VOLSTROF	1/20/00				
sheet index	revision sheet							type CUSTOMER Drawing		