

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
J	-	D3	REVISED	ECR-008942	15JUN15	KF	RK

Top view dimensions: 6.4, 3.2, 18.5 ±0.3, <29.7>, 45 ±0.3, <56>

Side view dimensions: 6.4, 3.2, 18.5 ±0.3, 45 ±0.3

Dimensions: 15, 11.8, 5.2, 1, 5.2, 1.85 ±0.3, 6.25, 49.9, 18 ±0.3, 2.3 ±0.3, 0, 3.5, 6.6, 9.1, 14.6, 17.1, 19.6, 22.1, 24.6, 27.6, 30.1, 32.6, 35.1, 37.6

<MOUNTING DIMENSIONS FOR P. C. BOARD; TOLERANCE±0.1>
 プリント基板取付寸法図
 一般公差: ±0.1
 (公差は累積しないこと)

Dimensions: 26xØ1.1, 6.25, 2xØ3.5, 49.9, 4.5, 9.6, 15 MAX

△ MUST BE KEPT BETWEEN [X] AND 2
 2. THE MATING PLUG HSG.PART NUMBER: 178747, 917850
 3. RECOMMENDED MOUNTING SCREW; 3mm DIA, 6mm LENGTH (MAX.)
 PAN HEAD, CLASS 2 TAPPING SCREW SPECIFIED IN JIS B1115, B1122
 (TIGHTENING TORQUE; 0.4N-m (4Kg-cm) MAX)
 △ CIRCUIT NUMBER
 POWER CIRCUIT NO. ⑳~㉔
 SIGNAL CIRCUIT NO. ①~㉒
 △ INDICATED PREFIX AND ID MARK OF PRODUCT P/N BY HOT MARK
 6. APPLICABLE PRODUCT SPEC NO.: 108-5280, 108-5342

△ [X] 面から2mmの範囲で測定
 2. 嵌合相手ハウジング型: 178747, 917850
 3. 推奨取付ねじ: JIS B1115, B1122 タッピングねじ, なべ2種
 呼び径3, 長さ6mm以下 (締付けトルク; 0.4N-m (4kg-cm) 以下)
 △ 回路番号: 下図参照のこと
 パワー回路 ⑳~㉔
 シグナル回路 ①~㉒
 △ 適用製品型番のアプリフィックス及びIDマークを
 カワーホットマークにて表示
 6. 適用製品規格番号: 108-5280, 108-5342

A-A dimensions: 8 ±0.4, 4 ±0.5, 4 ±0.3, 6.4, 4.5, 4.5, 6.4

B-B dimensions: 7.1 ±0.4, 4 ±0.5, 4 ±0.3, 6.4, 4.5, 6.4

Pin layout: 1 2 3 4 5 6 7 8 9 10 11 23 24
 12 13 14 15 16 17 18 19 20 21 22 25 26

SIZE	FINISH	PLATING	POWER CIRCUIT NO.	SIGNAL CIRCUIT NO.	HOUSING COLOR	P/N
0	PRE-TIN × 21	SELECTIVE-TIN [MATTE] SELECTIVE GOLD × 5	---	⑱ ⑲ ⑳ ㉑ ㉒	BLACK 黒色	2-5178209-2
0	PRE-TIN × 21	PRE-TIN × 21 SELECTIVE GOLD × 5	---	⑱ ⑲ ⑳ ㉑ ㉒	LIGHT GRAY 淡灰色	2-5178209-9
2	TIN-LEAD	PRE-TIN × 21 SELECTIVE GOLD × 5	---	⑱ ⑲ ⑳ ㉑ ㉒	BLACK 黒色	2-178209-2
2	TIN-LEAD	PRE-TIN × 21 SELECTIVE GOLD × 5	---	⑱ ⑲ ⑳ ㉑ ㉒	LIGHT GRAY 淡灰色	2-178209-9
0	PRE-TIN × 26	---	---	---	LIGHT GRAY 淡灰色	178209-9
0	PRE-TIN × 26	---	---	---	ORANGE 橙色	178209-8
MARKING	SOLDERING SIDE 半田付け部	CONTACT SIDE 接触部側	POWER CIRCUIT NO. パワー回路	SIGNAL CIRCUIT NO. シグナル回路	HOUSING COLOR ハウジング色	P/N
MARKING	CONTACT FINISH コンタクト仕上げ		CIRCUIT NO. OF GOLD 全メッキ端子使用回路番号			

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: 単位: 純 mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差	DWN 02JUN11 T.SHINOHARA	TE Connectivity
0 PLC ±	0 PLC ±	CHK 02JUN11 K.BETSUI	NAME 名称
1 PLC ±	1 PLC ±	APVD 02JUN11 K.BETSUI	26POSITION CAP HOUSING ASSEMBLY
2 PLC ±	2 PLC ±	PRODUCT SPEC 製品規格	040/070 SERIES HYBRID I/O CONNECTOR
3 PLC ±	3 PLC ±	APPLICATION SPEC 取付適用規格	LOWPRO FILE
4 PLC ±	4 PLC ±	WEIGHT	SIZE A2
ANGLES ±	ANGLES ±	CUSTOMER DRAWING	CAGE CODE 00779
FINISH 仕上	FINISH 仕上	SEE TABLE 表参照	DRAWING NO. 番号 C=178209
MATERIAL 材料	MATERIAL 材料	HOUSING: PBT	RESTRICTED TO
CONTACT: BRASS	CONTACT: BRASS		SCALE 2:1 SHEET 1 OF 1 REV D3

1471-9 (3/11)

178209

A