

Surge protection device - TT-ST-M-2-PE-24AC - 2858920

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



TERMITRAB, spring-cage modular terminal block with integrated surge protection and disconnect knives, for assembly on NS 35/7.5, voltage U_N 24 V DC, terminal width: 6.2 mm, cover width: 2.2 mm

Product Features

- ✓ Multi-stage modular terminal blocks with spring-cage connection
- ✓ Disconnection of signal circuits by disconnect knife



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	31.47 GRM
Custom tariff number	85363030
Country of origin	Germany

Technical data

Dimensions

Height	100 mm
Width	6.2 mm
Depth	63.5 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Degree of protection	IP20

General

Housing material	PA 6.6
Inflammability class according to UL 94	V2

Surge protection device - TT-ST-M-2-PE-24AC - 2858920

Technical data

General

Color	black
Standards for air and creepage distances	EN 60664-1
	IEC 60664-1
Surge voltage category	III
Pollution degree	2
Mounting type	DIN rail: 35 mm
Type	Double-level terminal block with disconnect knife
Number of positions	2
Direction of action	Line-Line & Line-Earth Ground

Protective circuit

IEC test classification	C1
	C2
	C3
	D1
VDE requirement class	C1
	C2
	C3
	D1
Nominal voltage U_N	24 V AC
Maximum continuous operating voltage U_C	45 V DC
	31 V AC
Maximum continuous voltage U_C (wire-wire)	45 V DC
	31 V AC
Nominal current I_N	350 mA (45°C)
Operating effective current I_C at U_C	$\leq 10 \mu A$
Residual current I_{PE}	$\leq 2 \mu A$
Nominal discharge current I_n (8/20) μs (Core-Core)	5 kA
Nominal discharge current I_n (8/20) μs (Core-Earth)	5 kA
Total surge current (8/20) μs	10 kA
Total surge current (10/350) μs	2 kA
Max. discharge current I_{max} (8/20) μs maximum (Core-Core)	5 kA
Max. discharge current I_{max} (8/20) μs maximum (Core-Earth)	5 kA
Nominal pulse current I_{an} (10/1000) μs (Core-Core)	100 A
Nominal pulse current I_{an} (10/1000) μs (Core-Earth)	200 A (in total)
Impulse discharge current (10/350) μs , peak value I_{imp}	1 kA (per path)
Output voltage limitation at 1 kV/ μs (Core-Core) spike	$\leq 55 V$

Surge protection device - TT-ST-M-2-PE-24AC - 2858920

Technical data

Protective circuit

Output voltage limitation at 1 kV/ μ s (Core-Earth) spike	≤ 600 V
Output voltage limitation at 1 kV/ μ s (Core-Core) static	≤ 55 V
Output voltage limitation at 1 kV/ μ s (Core-Earth) static	≤ 600 V
Residual voltage at I_n (conductor-conductor)	≤ 55 V
Voltage protection level U_p (Core-Core)	≤ 80 V (C2 (10 kV/5 kA))
	≤ 40 V (stat.)
Voltage protection level U_p (Core-Earth)	≤ 600 V (C2 (10 kV/5 kA))
Response time t_A (Core-Core)	≤ 1 ns
Response time t_A (Core-Earth)	≤ 100 ns
Input attenuation a_E , sym.	typ. 1 dB (400 kHz/50 Ω)
	typ. 0.4 dB (170 kHz/150 Ω)
	typ. 0.1 dB (40 kHz/600 Ω)
Cut-off frequency f_g (3 dB), sym. in 50 Ohm system	3.5 MHz
Cut-off frequency f_g (3 dB), sym. in 150 Ohm system	1.1 MHz
Cut-off frequency f_g (3 dB), sym. in 600 Ohm system	typ. 280 kHz
Capacity (Core-Core)	2 nF
Capacity (Core-Earth)	2 pF
Resistance in series	6.6 Ω ± 20 % (per path)
	6.6 Ω
Surge protection fault message	None
Max. required back-up fuse	370 mA
Surge carrying capacity in acc. with IEC 61643-21 (Core-Core)	C2 (10 kV/5 kA)
	C3 (100 A)
Surge carrying capacity in acc. with IEC 61643-21 (Core-Earth)	C2 (10 kV/5 kA)
	D1 (1 kA)
	C3 (100 A)

Connection data

Connection method	Spring-cage connection
Connection type IN	Spring-cage
Connection type OUT	Spring-cage
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

Surge protection device - TT-ST-M-2-PE-24AC - 2858920

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807

ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

GOST / UL Listed / GL

Ex Approvals

Approvals submitted

Approval details

Surge protection device - TT-ST-M-2-PE-24AC - 2858920

Approvals


GOST

UL Listed

GL

Drawings

Dimensioned drawing



Circuit diagram

