

#### Rail D-Sub Backshells

TE Internal #: 2-2308265-0

Rectangular Connector Hardware, Quick Lock Pins, -40 – 90 °C [-40

– 194 °F], Rail D-Sub Backshells

View on TE.com >



Connectors > Rectangular Connectors > Rectangular Connector Accessories > Rectangular Connector Hardware >

Quick Lock Pins for D-Sub with Threaded Inserts











Connector Hardware Type: Quick Lock Pins

Operating Temperature Range: -40 - 90 °C [-40 - 194 °F]

All Quick Lock Pins for D-Sub with Threaded Inserts (10)

### **Features**

### **Mechanical Attachment**

Thread Size	None
Connector Hardware Type	Quick Lock Pins
Usage Conditions	
Operating Temperature Range	-40 - 90 °C[-40 - 194 °F]

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Pb (3.5% in Component Part) Article Safe Usage Statements:



Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts











Also in the Series | Rail D-Sub Backshells









Connector Strain Relief(53)

Crimp D-Sub Connectors(10)

D-Sub Connector Contacts(5)



Insertion & Extraction Tools(2)



Rectangular Connector Hardware(19)

# Customers Also Bought



TE Part #1-2308272-1
CABLE CLAMPS (CASE RAW)



TE Part #1-2308273-1 QL-SET VAR A W/STP MO FOR COMBLOCK M3THD



TE Part #2-2308341-0 FULL METAL HOODS SIZE 2-10 (RAW 135 DEG)



TE Part #1-1879216-1 CPF 0402 63K4 0.1% 25PPM 1K RL



TE Part #1-2308290-1 QL-SET FOR VARIAN C VW REAR WALL MOUNTG



TE Part #3-2176400-7 3540 33R 1%



TE Part #5-1879334-2 CPF 0603 6R81 1% 50PPM 1K RL



TE Part #NB-PTCO-045
Pt100, 2.0x10.0, Class A, PTFB101AG00

## **Documents**



## **Product Drawings**

**QL SET FOR VARIANT B 10** 

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2-2308265-0\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-2308265-0\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-2308265-0\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

Rail D-Sub Backshells Flyer

English