

Touch panel - TP 3057T - 2700906

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 14.5 cm (5.7") graphics-capable TFT display, 65,535 colors, 320 x 240 pixels, 1 x Ethernet, 2 x USB, and integrated runtime of the Visu+ visualization software

Product Features

- Easy installation, low installation depth, and compact design
- Short startup time
- Visu+ RT and AX OPC server integrated as standard in all devices
- Display available in sizes from 14.5 cm (5.7") to 30.7 cm (12")
- Can be extended with external CF card
- Can be extended with external CF card
- Energy efficient due to LED backlighting

Key commercial data

| | |
|----------------------|----------|
| Packing unit | 1 pc |
| Custom tariff number | 84714100 |
| Country of origin | Germany |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| | |
|---------------------------------------|--|
| External dimension, width | 203 mm |
| External dimension, height | 147 mm |
| External dimension, depth | 5 mm |
| Note regarding external dimension | Dimensions of the front plate |
| Installation dimension, width | 195 mm |
| Installation dimension, height | 139 mm |
| Note regarding installation dimension | 55 mm, approximately with fieldbus interface |

Display

Touch panel - TP 3057T - 2700906

Technical data

Display

| | |
|------------------------|-----------------------------------|
| Display | 14.5 cm/5.7" TFT active |
| Resolution | 320 x 240 Pixel (QVGA) |
| Backlighting | LED |
| Display backlight MTBF | 40000 h |
| Touch screen | Resistive industrial touch screen |
| Colors | 65,536 colors |

Computer data

| | |
|---------------------|------------------------------------|
| Processor | Xscale® PXA320, 806 MHz |
| RAM | 128 MB SDRAM |
| Mass storage | 1 GB Flash |
| Interfaces | 2x USB Host 1.1, 1x Compact Flash® |
| Optional interfaces | 1x CF card, type I and II |
| Network | 1 x Ethernet (10/100 Mbps), RJ45 |
| Operating systems | Windows CE 6.0 |
| Power supply unit | 24 V DC ±20 % |
| Power consumption | 12 VA |

General

| | |
|---------------|-----------------------------|
| Mounting type | Installation in front plate |
| Weight | 1000 g |

Ambient conditions

| | |
|--|--------------------------------|
| Degree of protection | IP65 (front), IP20 (back) |
| Ambient temperature (operation) | 0 °C ... 50 °C |
| Ambient temperature (storage/transport) | -25 °C ... 70 °C |
| Permissible humidity (operation) | 20 % ... 85 % (non-condensing) |
| Permissible humidity (storage/transport) | 20 % ... 85 % (non-condensing) |
| Vibration (operation) | DIN EN 60068-2-6 |
| Shock | DIN EN 60068-2-27 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27330202 |
| eCl@ss 4.1 | 27330202 |
| eCl@ss 5.0 | 27242215 |
| eCl@ss 5.1 | 27242301 |
| eCl@ss 6.0 | 27242301 |

Touch panel - TP 3057T - 2700906

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 7.0 | 27242301 |
| eCl@ss 8.0 | 27242301 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001426 |
| ETIM 3.0 | EC001426 |
| ETIM 4.0 | EC001426 |
| ETIM 5.0 | EC001414 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43211903 |
| UNSPSC 13.2 | 43201404 |

Approvals

Approvals


Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approvals submitted

Approval details

| |
|---|
| UL Listed  |
|---|

| |
|--|
| cUL Listed  |
|--|

Touch panel - TP 3057T - 2700906

Approvals

