2-2205131-6 - ACTIVE

TE Internal #: 2-2205131-6 INDUSTRIAL MINI I/O Cable Assembly, 8 Positions, 32.8 ft [10 m], 1 Gb/s, Black Cable, Shielded, 26 AWG, .129 mm², Twisted Pair View on TE.com >



Cable Assemblies > Copper Cable Assemblies > Pluggable I/O Cable Assemblies



Cable Assembly Type: INDUSTRIAL MINI I/O

Equalized: No

Wire Size: .129 mm²

Outside Cable Diameter: 6.2 mm [.244 in]

Features

Product Type Features

Latching Style	Slide Latch	
Cable Assembly Category	Industry Standard	
Cable Assembly Type	INDUSTRIAL MINI I/O	
Connector Type (End A)	INDUSTRIAL MINI I/O Plug	
Connector Type (End B)	INDUSTRIAL MINI I/O Plug	
Cable Style	Twisted Pair	
Configuration Features		
Number of Positions	8	
Number of Signal Positions	8	
Electrical Characteristics		
Impedance	100 Ω	
Signal Characteristics		
Data Rate	1 Gb/s	
Body Features		
Shield Material	Copper Alloy	
Jacket Material	PUR	
Equalized	No	
Cable Color	Black	
Cable Flammability Rating	UL 444	

2-2205131-6

INDUSTRIAL MINI I/O Cable Assembly, 8 Positions, 32.8 ft [10 m], 1 Gb/s, Black Cable, Shielded, 26 AWG, .129 mm², Twisted Pair



Contact Features

Contact Mating Area Plating Material Thickness	19.68 μm[.5 μin]
Contact Mating Area Plating Material	Gold
Housing Features	
Housing Material	Thermoplastic
Dimensions	
Wire Size	.129 mm ²
Outside Cable Diameter	6.2 mm[.244 in]
Operation/Application	
Shielded	Yes
Halogen Free	Yes
Industry Standards	
Performance Category	Cat 5e
Other	
Cable Assembly Configuration	Double Ended
Cable Assembly Length	10 m[32.8 ft]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC	
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.	
Solder Process Capability	Not applicable for solder process capability	

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products

2-2205131-6

INDUSTRIAL MINI I/O Cable Assembly, 8 Positions, 32.8 ft [10 m], 1 Gb/s, Black Cable, Shielded, 26 AWG, .129 mm², Twisted Pair



will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Customers Also Bought



Female, Straight	



Documents

Product Drawings CA MINI IO MINI IO TYPE I

English

Product Specifications Application Specification English