

“Stay Connected” with



HEYware Products




a PennEngineering® Company



Heyco® Self-Closing Braided Sleeving

MAXIMUM DIAMETER		PART NO. Black	DESCRIPTION	PART DIMENSIONS				INSTALLATION TOOL Part No.
in.	mm			Nominal Diameter		Spool Qty		
				in.	mm	ft.	m	
.28	7,0	8880	SCBS-250 BLACK	.25	6,4	100	30,5	8889
.39	10,0	8881	SCBS-375 BLACK	.38	9,7			
.55	14,0	8882	SCBS-500 BLACK	.50	12,7	100	30,5	8890
.67	17,0	8883	SCBS-625 BLACK	.63	16,0			
.79	20,0	8884	SCBS-750 BLACK	.75	19,1	100	30,5	8891
1.02	26,0	8885	SCBS-1000 BLACK	1.00	25,4			
1.30	33,0	8886	SCBS-1250 BLACK	1.25	31,8	100	30,5	8892
1.57	40,0	8887	SCBS-1500 BLACK	1.50	38,1			
2.05	52,0	8888	SCBS-2000 BLACK	2.00	50,8	100	30,5	*

*No tool provided for the 2.00" bundle.



- Self-Closing Braided Sleeving (SCBS) can be used on pre-terminated wires due to the self closing concept. SCBS makes maintenance fast and effective. Simply open SCBS, make adjustments, and reinstall after service.
- The installation tool makes routing wire fast and easy.
- The 25% edge overlap allows coverage around inline connectors/plugs.
- Full cable flexibility is maintained in any direction, even at low temperatures. Wires encased in Heyco Self Closing Braided Sleeving can flex and bend as readily as if they had no protective oversleeving. Bundles can be flexed repeatedly without damage.
- Tough, cut-resistant sleeving is designed for protecting wire bundles and harnesses, hoses, tubing, and cable assemblies from mechanical damage and environmental hazards.
- Preferred cutting method: hot knife.

Heyco® Braided Sleeving

BUNDLE RANGE				PART NO.		DESCRIPTION	PART DIMENSIONS			
Minimum Diameter		Maximum Diameter		Black	FR Black		Nominal Diameter		Quantity Per Spool	
in.	mm.	in.	mm.			in.	mm.	ft.	mtrs.	
.09	2,3	.25	6,4	8980	8983	BS 125	.13	3,2	1000	305
.13	3,2	.44	11,1	8985	8988	BS 250	.25	6,4		
.25	6,4	.75	19,1	8990	8993	BS 500	.50	12,7	500	152
.50	12,7	1.25	31,8	8995	8998	BS 750	.75	19,1		
.75	19,1	1.75	44,5	9000	9003	BS 1250	1.25	31,8	250	76
1.25	31,8	2.75	69,9	9005	9008	BS 1750	1.75	44,5		
1.50	38,1	3.50	88,9	9010	9013	BS 2.0	2.00	50,8	200	61

Standard color black.

FR sleeving flammability rating-UL VW-1.



- Braided sleeve slips on quickly and is self-fitting over irregular shapes and contours. No wire pulling compounds are required due to its low surface friction. Slight tensioning after application makes for an even tighter fit.
- Expandable up to three times its own diameter, the open-weave construction can fit many applications, simplifying inventory. The open-weave allows for easy inspection of sleeved components and easy break out of individual cables.
- Full cable flexibility is maintained in any direction, even at low temperatures. Wires encased in Heyco Braided Sleeving can flex and bend as readily as if they had no protective oversleeving. Bundles can be flexed repeatedly without damage.
- Tough, cut-resistant sleeving is designed for protecting wire bundles and harnesses, hoses, tubing, and cable assemblies from mechanical damage and environmental hazards.
- Preferred cutting method: hot knife.

SC Braided Sleeving		Braided Sleeving	
Material	Polyester	Materials	Polyester Monofilament Yarns or Flame Retardant Polyester Yarn
Flammability Rating	UL 94 V2	Certifications	Recognized under the Component Program of Underwriters' Laboratories File E173954
Temperature Range	-58°F (-50°C) to 302°F (150°C)	Monofilament Dia.	.010"
		Temperature Range	-103°F (-75°C) to 257°F (125°C)