## 1-281838-2 ACTIVE

## AMPMODU | AMPMODU HE 13/HE 14

TE Internal #: 1-281838-2


Housing, Receptacle, Wire-to-Board, 12 Position, .1 in [2.54 mm] Centerline, Insulation Displacement (IDC), 1 Row, Blue, AMPMODU

HE 13/HE 14

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings > HE13/HE14 Crimp Housings



Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 12

Centerline (Pitch): 2.54 mm [.1 in]

All HE13/HE14 Crimp Housings (18)

## **Features**

## **Product Type Features**

Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	12
Number of Rows	1
Body Features	
Primary Product Color	Blue

## **Contact Features**

Contact Layout	Inline
Contact Type	Socket
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	3 A

#### **Termination Features**



Termination Method to Wire & Cable  Mechanical Attachment  Strain Relief Panel Mount Feature PCB Mount Retention Without PCB Mount Retention With  Housing Features  Housing Features  Housing Factures  Housing Material Centerlina (Pitch) Dimensions  Connector Length Connector Height Wire Size Row-to-Row Spacing Usage Conditions  Operating Temperature Range Operation/Application Circuit Application Circuit Application Signal Industry Standards Glow Wire Rating UL Flammability Rating Packaging Features Packaging Features Packaging Guantity Packaging Method  Without Without With With With With With With Housing Material PBT GF PBT GF PBT GF PBT GF  Operation Closed PBT GF  Operation (Pitch) Dimensions  00.48 mm[1.2 in]  00.8 – .22 mm²  Row-to-Row Spacing Department (PICC) Packaging Method Packaging Guantity Packaging Method Packaging Pa		
Strain Relief Without Panel Mount Feature Without PCB Mount Retention Without  Mating Retention With  Housing Features  Housing Fantry Configuration Both Ends Closed Housing Material PBT GF  Centerline (Pitch) 2.54 mm[.1 in]  Dimensions  Connector Length 30.48 mm[1.2 in]  Connector Height 15 mm[.591 in]  Wire Size .08 – .22 mm²  Row to Row Spacing 2.54 mm[.1 in]  Usage Conditions  Operating Temperature Range -55 – 125 °C[-67 – 257 °F]  Operation/Application  Circuit Application Signal  Industry Standards  Glow Wire Rating Standard Part - Not Glow Wire  UL Flammability Rating UL 94V 0  Packaging Features  Packaging Quantity 500	Termination Method to Wire & Cable	Insulation Displacement (IDC)
Panel Mount Feature Without  PCB Mount Retention Without  Mating Retention With  Housing Features  Housing Features  Housing Entry Configuration Both Ends Closed  Housing Material PBT GF  Centerline (Pitch) 2.54 mm[.1 in]  Dimensions  Connector Length 30.48 mm[1.2 in]  Connector Height 15 mm[.591 in]  Wire Size 08 22 mm?  Row-to-Row Spacing 2.54 mm[.1 in]  Usage Conditions  Operating Temperature Range -55 - 125 °C[-67 - 257 °F]  Operation/Application  Circuit Application Signal  Industry Standards  Glow Wire Rating Standard Part - Not Glow Wire  UL Flammability Rating UL 94V-0  Packaging Features  Packaging Quantity 500	Mechanical Attachment	
PCB Mount Retention With  Mating Retention With  Housing Features  Housing Entry Configuration Both Ends Closed  Housing Material PBT GF  Centerline (Pitch) 2.54 mm[.1 in]  Dimensions  Connector Length 30.48 mm[1.2 in]  Connector Height 15 mm[.591 in]  Wire Size .08 – .22 mm²  Row-to-Row Spacing 2.54 mm[.1 in]  Usage Conditions  Operating Temperature Range -55 – 125 °C[-67 – 257 °F]  Operation/Application  Circuit Application Signal  Industry Standards  Glow Wire Rating Standard Part - Not Glow Wire  UL Flammability Rating UL 94V-0  Packaging Quantity 500	Strain Relief	Without
Mating Retention With  Housing Features  Housing Entry Configuration Both Ends Closed  Housing Material PBT GF  Centerline (Pitch) 2.54 mm[.1 in]  Dimensions  Connector Length 30.48 mm[1.2 in]  Connector Height 15 mm[.591 in]  Wire Size	Panel Mount Feature	Without
Housing Features  Housing Entry Configuration Both Ends Closed  Housing Material PBT GF  Centerline (Pitch) 2.54 mm[.1 in]  Dimensions  Connector Length 30.48 mm[1.2 in] Connector Height 15 mm[.591 in] Wire Size .0822 mm² Row-to-Row Spacing 2.54 mm[.1 in]  Usage Conditions  Operating Temperature Range -55 - 125 °C[-67 - 257 °F]  Operation/Application  Circuit Application  Signal  Industry Standards  Glow Wire Rating UL Flammability Rating VL 94V-0  Packaging Features  Packaging Quantity 500	PCB Mount Retention	Without
Housing Entry Configuration  Housing Material  PBT GF  Centerline (Pitch)  2.54 mm[.1 in]  Dimensions  Connector Length  30.48 mm[1.2 in]  Connector Height  15 mm[.591 in]  Wire Size  .0822 mm²  Row-to-Row Spacing  2.54 mm[.1 in]  Usage Conditions  Operating Temperature Range  -55 - 125 °C[ 67 - 257 °F]  Operation/Application  Circuit Application  Signal  Industry Standards  Glow Wire Rating  UI Plammability Rating  VI 194V-0  Packaging Features  Packaging Quantity  Standard Part - Not Glow Wire	Mating Retention	With
Housing Material PBT GF  Centerline (Pitch) 2.54 mm[.1 in]  Dimensions  Connector Length 30.48 mm[1.2 in]  Connector Height 15 mm[.591 in]  Wire Size .08 – .22 mm²  Row-to-Row Spacing 2.54 mm[.1 in]  Usage Conditions  Operating Temperature Range -55 – 125 °C[-67 – 257 °F]  Operation/Application  Circuit Application Signal  Industry Standards  Glow Wire Rating Standards  Glow Wire Rating UL Plammability Rating UL 94V-0  Packaging Features  Packaging Quantity 500	Housing Features	
Centerline (Pitch)  Dimensions  Connector Length  Connector Height  15 mm[.591 in]  Wire Size  Row-to-Row Spacing  2.54 mm[.1 in]  Usage Conditions  Operating Temperature Range  Circuit Application  Circuit Application  Industry Standards  Glow Wire Rating  UL Flammability Rating  Packaging Quantity  2.54 mm[.1 in]  Signal  Letter Sig	Housing Entry Configuration	Both Ends Closed
Dimensions  Connector Length 30.48 mm[1.2 in]  Connector Height 15 mm[.591 in]  Wire Size .0822 mm²  Row-to-Row Spacing 2.54 mm[.1 in]  Usage Conditions  Operating Temperature Range -55 - 125 °C[-67 - 257 °F]  Operation/Application  Circuit Application Signal  Industry Standards  Glow Wire Rating Standard Part - Not Glow Wire  UL Flammability Rating UL 94V-0  Packaging Features  Packaging Quantity 500	Housing Material	PBT GF
Connector Length Connector Height 15 mm[.591 in] Wire Size .0822 mm² Row-to-Row Spacing 2.54 mm[.1 in] Usage Conditions Operating Temperature Range -55 - 125 °C[-67 - 257 °F] Operation/Application Circuit Application Signal Industry Standards Glow Wire Rating UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 500	Centerline (Pitch)	2.54 mm[.1 in]
Connector Height 15 mm[.591 in]  Wire Size .0822 mm²  Row-to-Row Spacing 2.54 mm[.1 in]  Usage Conditions  Operating Temperature Range -55 - 125 °C[-67 - 257 °F]  Operation/Application  Circuit Application Signal  Industry Standards  Glow Wire Rating Standard Part - Not Glow Wire  UL Flammability Rating UL 94V-0  Packaging Features  Packaging Quantity 500	Dimensions	
Wire Size  Row-to-Row Spacing  2.54 mm[.1 in]  Usage Conditions  Operating Temperature Range  -55 – 125 °C[-67 – 257 °F]  Operation/Application  Circuit Application  Signal  Industry Standards  Glow Wire Rating  UL Flammability Rating  Packaging Features  Packaging Quantity  500	Connector Length	30.48 mm[1.2 in]
Row-to-Row Spacing  Usage Conditions  Operating Temperature Range  -55 - 125 °C[-67 - 257 °F]  Operation/Application  Circuit Application  Signal  Industry Standards  Glow Wire Rating  UL Flammability Rating  Packaging Features  Packaging Quantity  2.54 mm[.1 in]  2.54 mm[.1 in]  Standard Part - 257 °F]  UL 94V-0  Packaging Guantity	Connector Height	15 mm[.591 in]
Usage Conditions  Operating Temperature Range -55 – 125 °C[-67 – 257 °F]  Operation/Application  Circuit Application Signal  Industry Standards  Glow Wire Rating Standard Part - Not Glow Wire  UL Flammability Rating UL 94V-0  Packaging Features  Packaging Quantity 500	Wire Size	.08 – .22 mm²
Operating Temperature Range -55 – 125 °C[-67 – 257 °F]  Operation/Application  Circuit Application  Signal  Industry Standards  Glow Wire Rating  UL Flammability Rating  UL 94V-0  Packaging Features  Packaging Quantity  500	Row-to-Row Spacing	2.54 mm[.1 in]
Operation/Application  Circuit Application  Signal  Industry Standards  Glow Wire Rating  UL Flammability Rating  UL 94V-0  Packaging Features  Packaging Quantity  500	Usage Conditions	
Circuit Application  Industry Standards  Glow Wire Rating  UL Flammability Rating  Packaging Features  Packaging Quantity  Signal  UL 94V-0  Standard Part - Not Glow Wire  UL 94V-0	Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Industry Standards  Glow Wire Rating  UL Flammability Rating  UL 94V-0  Packaging Features  Packaging Quantity  500	Operation/Application	
Glow Wire Rating  UL Flammability Rating  Packaging Features  Packaging Quantity  Standard Part - Not Glow Wire  UL 94V-0  500	Circuit Application	Signal
UL Flammability Rating  Packaging Features  Packaging Quantity  500	Industry Standards	
Packaging Features  Packaging Quantity  500	Glow Wire Rating	Standard Part - Not Glow Wire
Packaging Quantity 500	UL Flammability Rating	UL 94V-0
	Packaging Features	
Packaging Method Box	Packaging Quantity	500
	Packaging Method	Box

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	



Current ECHA Candidate List: JUNE 2023

(235)

Candidate List Declared Against: JUNE

2023 (235)

Does not contain REACH SVHC

Halogen Content Not Low Halogen - contains Br or Cl > 900 ppm.

Solder Process Capability Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

## Compatible Parts







## Also in the Series | AMPMODU HE 13/HE 14



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(83)



Wire-to-Board Connector Assemblies & Housings(131)



# Customers Also Bought






TE Part #3-640620-8 08P MTA100 CONN ASSY F/T RED













#### **Documents**

## **Product Drawings**

HOUSING HE13 HE14 COSI 12 P

English

#### **CAD Files**

3D PDF

English

**Customer View Model** 

ENG\_CVM\_1-281838-2\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_1-281838-2\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_1-281838-2\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## **Product Specifications**

**Product Specification** 

French

**Product Environmental Compliance** 

MD\_1-281838-2\_10282015730\_dmtec

English

MD\_1-281838-2\_10282015730\_dmtec

English

Housing, Receptacle, Wire-to-Board, 12 Position, .1 in [2.54 mm] Centerline, Insulation Displacement (IDC), 1 Row, Blue, AMPMODU HE 13/HE 14

