



REED SWITCH DEVELOPMENTS CORP.

2524 Norwood Court
Racine, WI 53403
Ph: (262)883-9060

sales@reedswitchdevelopments.com

SPECIFICATION SHEET

2250-1901-400

Alternate Part Number:

AM2250-1901-10K01

Active / Equivalent Part Numbers:

2250-1901-400 - KIT - Contains

(1) 2250-1901-100 - Magnetic Reed Sensor

(1) 2250-4002-000 - Magnetic Actuator


AM2250-1901-10K01 - KIT - Contains

(1) AM2250-1901-10-01 - Magnetic Reed Sensor

(1) AM2250-4002-00-01 - Magnetic Actuator

Sensor (Reed) - Specifications		1901		
Physical	Configuration	SPDT		
	Form	C		
	Contact Position	OFFSET		
	Glass L	14.00	mm	
	Glass D	2.30	mm	
	Total L*	55.00	mm	
	Wire D	0.53	mm	
	Gap Location	OFFSET		
	Mount Spec*	THRU		
	Contact Material	RHODIUM		
	Max Vibration Resistance	20	G	
	Max Shock Resistance (11ms)	50	G	
	Lead Tensile Strength	N/A	KG	
	Operating	Pull in (+/- 2AT)*	15-20	AT
		Drop out*	5	AT
Operate Time		2.0	ms	
Bounce Time		0.60	ms	
Release Time		0.50	ms	
Resonant Frequency		N/A	Hz	
Max Operating Frequency		250	Hz	
Operating Temperature Range		-40 - 105	°C	
Storage Temperature		N/A	°C	
Electrical		DC Contact Rating	20	W
	AC Contact Rating	20	VA	
	DC Switching Voltage	150	VDC	
	AC Switching Voltage	150	VAC	
	DC Switching Current	1.00	A	
	AC Switching Current	1.00	A	
	DC Max Carry Current	2.00	A	
	AC Max Carry Current	2.00	A	
	Min Breakdown Voltage	200	VDC	
	Max Initial Contact Resistance	150	mOhm	
	Typical Initial Contact Resistance	N/A	mOhm	
	Max Contact Capacitance	0.80	pF	
	Min Insulation Resistance	10 ⁹	Ohm	

* Pre-processed, bare reed element



All measurements are in Inches [millimeters]

Sensor - Wire/Cable Characteristics (cont.)

Type	Wire
Conductor Count	3
Length	6.0"/152.4mm
Colors	RED, BLK, WHT
Insulation Material	PVC
Gauge	24 AWG
Stranded Copper	7 STR-TC
Maximum Temp	105°C

Conductor Configuration

Common (COM) - WHITE
Normally Open (NO) - RED
Normally Closed (NC) - BLACK

Housing Characteristics 2250

Cylindrical Threaded (5/16-24)	
Length	1.500"/31.75mm
Diameter	0.313"/7.95mm
Material	Aluminum

Standard Actuator: 2250-4002-000

Specifications	Description	UM	
Physical/Magnetic	Magnetic Orientation	Through Length	
	Max Operating Temp.	975/525	°F/°C
	Curie Temp.	1580/860	°F/°C
	BR max	12.8	kGauss
	BH max	5.5	MGOe
	Coercive Force Hc	640	kOe
	Intrinsic Coercive Force Hci	640	kOe

Std. Sensor/Actuator - Min. Actuation Dist.

2250-4002-000	0.25"/6.4mm
---------------	-------------

Assembly Certifications

UL Recognized (File #: E102207)	Y
RoHS / REACH Compliant	Y
Conflict Free Material	Y

REV DATE: 10/06/2021

DISCLAIMER NOTICE: INFORMATION FURNISHED IS PROPRIETARY, AND IS BELIEVED TO BE ACCURATE AND RELIABLE, AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IT SHALL BE THE RESPONSIBILITY OF THE BUYER TO ENSURE THAT THE GOODS ARE SUFFICIENT AND SUITABLE FOR THE PURPOSE OR PURPOSES INTENDED (WHETHER BY THE BUYER OR BY ANY THIRD PARTY) AND THAT THEIR CAPACITY AND PERFORMANCE IS NOT ADVERSELY AFFECTED BY ANY ITEMS USED IN THEIR INSTALLATION (WHERE RELEVANT) AND/OR IN CONNECTION WITH THEM.

WBE Certified - State of Wisconsin - MFR CAGE CODE: 32604

www.reedswitchdevelopments.com