

UM-BASIC/PRO 72 FOOT KMGY - Foot element



2202020

<https://www.phoenixcontact.com/us/products/2202020>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Press-drawn section housings, DIN rail mounting, for the DIN rail, for mounting below UM-BASIC PROFILE (width: 72 mm), color: light grey (7035), Foot element



Your advantages

- Different base profiles, each with three PCB levels
- Module covers of different geometries can be positioned in any way
- Compatibility with many standard connection technologies
- Easy device mounting thanks to snap-mount principle (the sides are fixed without the aid of tools)
- High degree of flexibility, thanks to freely positionable covering hoods

Commercial data

Item number	2202020
Packing unit	1 pc
Minimum order quantity	10 pc
Note	Made to order (non-returnable)
Sales key	AC13
Product key	ACHDAC
GTIN	4055626005300
Weight per piece (including packing)	7.81 g
Weight per piece (excluding packing)	7.42 g
Customs tariff number	39269097
Country of origin	PL

UM-BASIC/PRO 72 FOOT KMGY - Foot element



2202020

<https://www.phoenixcontact.com/us/products/2202020>

Technical data

Notes

General	Refer to the data sheet for the range in the download area.
---------	---

Product properties

Product type	Base latches
Product family	UM-BASIC
Type	for the DIN rail, for mounting below UM-BASIC PROFILE (width: 72 mm)
Housing type	Press-drawn section housings
Housing series	UM-BASIC

Material specifications

Color	light grey (7035)
Flammability rating according to UL 94	V0
Surface characteristics	untreated
Housing material	Polyamide

Environmental and real-life conditions

Glow-wire test

Specification	IEC 60695-2-11:2014-02
Temperature	850 °C
Time of exposure	30 s

Thermal stability / ball thrust test

Specification	IEC 60695-10-2:2014-02
Temperature	125 °C
Test duration	1 h
Force	20 N

Mechanical strength / tumbling barrel

Specification	IEC 60068-2-31:2008-05
Height of fall	50 cm
Frequency	50

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C ... 55 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Relative humidity (storage/transport)	80 %

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

UM-BASIC/PRO 72 FOOT KMGY - Foot element



2202020

<https://www.phoenixcontact.com/us/products/2202020>

Packaging specifications

Type of packaging	packed in cardboard
Outer packaging type	Carton

UM-BASIC/PRO 72 FOOT KMGY - Foot element



2202020

<https://www.phoenixcontact.com/us/products/2202020>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2202020>



UL Recognized

Approval ID: FILE E 240868

UM-BASIC/PRO 72 FOOT KMGY - Foot element



2202020

<https://www.phoenixcontact.com/us/products/2202020>

Classifications

ECLASS

ECLASS-11.0	27182701
ECLASS-13.0	27190605

ETIM

ETIM 8.0	EC002779
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

UM-BASIC/PRO 72 FOOT KMGY - Foot element



2202020

<https://www.phoenixcontact.com/us/products/2202020>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

UM-BASIC/PRO 72 FOOT KMGY - Foot element



2202020

<https://www.phoenixcontact.com/us/products/2202020>

Accessories

SZF 0-0,4X2,5 - Screwdriver

1204504

<https://www.phoenixcontact.com/us/products/1204504>



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.4 x 2.5 x 75 mm, 2-component grip, with non-slip grip

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com